



**BASHLIN  
INDUSTRIES**  
GROVE CITY, PENNSYLVANIA  
UP / DOWN / ALL-AROUND QUALITY

# IMPORTANT CUSTOMER INFORMATION

Bashlin has supplied quality equipment to Linemen since 1926. You may be able to find products for less, but you will not buy any other Lineman's Equipment that works or wears better than Bashlin's right priced quality products produced in our manufacturing facilities in Grove City, Pennsylvania.

Linework is dangerous. Properly using these products and appropriate training are keys to your safety. To aid in product understanding, as well as proper use of these items, the following information boxes and product application symbols are located with the product write-ups. Please read and understand this information, as well as the material included with and attached to product BEFORE using these items. If there are questions, please contact us via the various methods listed at the bottom of the page.



## FALL ARREST

More than 2', but not more than 6' free fall. (Full body harness)



## POSITIONING

Maximum 2' free fall. (Positioning belts, Line belts)



## RETRIEVAL

For rescue from enclosed confined spaces. (Full body harness)



## NOT A SAFETY BELT

Not to be considered personal protective equipment.

## MANUFACTURER'S WARRANTY

The Manufacturer warrants equipment manufactured by it to be free from defects in material and workmanship under normal use and service, its obligation under this warranty being limited to replacing at its factory any part or parts which shall, within 30 days after delivery of such equipment to the original purchaser, be returned to it and which its examination shall disclose to its satisfaction to have been thus defective; this warranty being expressly in lieu of all other warranties, expressed or implied, and all other obligations or liabilities on its part.

**THE INFORMATION IN THIS CATALOG IS TO THE BEST OF OUR KNOWLEDGE CORRECT AT THE TIME OF PRINTING. WE RESERVE THE RIGHT TO MAKE IMPROVEMENTS AND CHANGES AS NECESSARY TO OUR PRODUCTS WITHOUT NOTICE.**

**WARRANTED AND ALL OTHER REPAIR WORK MUST BE DONE BY BASHLIN FACTORY PERSONNEL USING BASHLIN COMPONENTS.**

## TERMS AND CONDITIONS

**Pricing** - Prices are subject to change without notice. The cost of Bashlin products is as low as is consistent with quality merchandise. We encourage comparison.

**Payment** - Open account terms are available once credit has been established. Bashlin accepts all major credit cards and cash advance orders. On cash advance orders, overpayment of less than \$2.00 cannot be refunded.

**Shipping** - All freight terms are F.O.B. shipping point unless otherwise stated.

**Contested Shipments** - Any shipping or handling claims must be reported within 14 days of shipment. Claims not reported in this time period will not be allowed.

**Returned Goods** - Returns must be authorized prior to shipment to our warehouse. There is a handling charge on all returned goods.



119 West Pine Street, P.O. Box 867 Grove City, PA 16127  
Phone: 724.458.8340 Fax: 724.458.8342 bashlin@bashlin.com





# BASHLIN'S FALL PROTECTION AND CLIMBING EQUIPMENT REGULATIONS AND REQUIREMENTS

The equipment used by linemen, cablemen, arborists, and tower workers is manufactured in accordance with consensus standards as well as regulations developed by federal or state authorities. These regulations are important for you because they provide guidelines not only for the users, but also the manufacturers and your employer.

Consensus standards are voluntarily developed. They are approved by the users and manufacturers of the products. The standards are administered by such bodies as the American National Standards Institute, (ANSI) and the American Society of Testing and Materials (ASTM). Following are some consensus standards that apply to these products:

## ANSI STANDARDS

- ANSI/ASSP Z359.1 The fall protection code 
- ANSI Z1331.1 Safety requirements for arboricultural operations.
- ANSI A10.32 Standard for fall protection system used in construction  and demolition.


## ASTM STANDARD

- F887 Standard specifications for personal climbing equipment and harnesses.

## OSHA STANDARDS FOR GENERAL INDUSTRY

Government groups also write laws that they refer to as standards regarding such things as the use of these products. Many times, sections are based on the consensus standards. The difference is that they are mandatory.

Following are some standards that may apply to the users of these products.

- 1910.269 Electric power, generation, transmission and distribution.
- 1910.268 Telecommunications. 
- 1910.67 Vehicle mounted elevating and rotating platforms.
- 1910.140 Personal fall protection systems.

## OSHA STANDARDS FOR CONSTRUCTION

- 1926 Subpart M Fall protection.
- 1926.500 to 1926.503
- 1926.954 Personal protective equipment.

For more information, contact your corporate safety professional, supervisor, local OSHA office or insurance carrier.

To the best of our knowledge, Bashlin equipment meets or exceeds all applicable standards or laws at the time of manufacture.

Bashlin Industries Inc. utilizes Underwriters Laboratories  for independent 3rd party certification on many products. Look for the  symbol. Certificates of compliance available on request and on our website.



**WARNING:** Important information is included with each product. It must be read and understood prior to use. If none is included with your product, or if there are any questions, contact us immediately. Failure to understand the information, or be properly trained prior to using the product may cause accidents, injury, or death.

Linemen's  
Climbing  
Equipment

5

Fall Protection  
and Rescue Equipment  
for Lineworkers  
and General Industry

33

Bags, Buckets  
and Tool Carriers

57

Line Vehicle Equipment  
and Construction Tools

69

Electrical Personal  
Protective Equipment

79

Gloves, PPE, Books  
and Training

89






## LINEMEN'S CLIMBING EQUIPMENT

**Bashlin Industries, Inc.** manufactures quality tool belts, pole straps, and climbers for the professional lineworker. These products are designed for comfort and durability. We offer a complete assortment of climbing products for workers ranging from apprentice to journeyman.

**Climbing is serious business.** We recommend that you properly care for this equipment; your personal safety depends on it. Learn how to properly use, inspect and maintain your tools. Guidelines appear in this catalog; more detailed information is included with Bashlin products. Remember, when in doubt, DON'T.

# SIZING TOOL BELTS

Bashlin belts are sized using the measurement between the 2 D-Rings on the main portion of the belt (A).



2 D-Ring and 4 D-Ring belts are sized identically.

Measure for summer clothing. If the belt is the correct size, there will be ample adjustment for the relatively limited time it will be used in the colder weather.

If a belt is sized correctly, the hip D-Rings will point straight ahead, and the tongue adjustment will be in the center hole (B).



CORRECTLY SIZED TOOL BELT

## USE BASHLIN'S LINEMAN'S SIZING BELT (LSB) (E)


Estimate the correct size of your belt and adjust the LSB to the size you believe your belt should be.

Place the LSB on your hips at the location where your tool belt is worn (F).

By trial and error, change the length of the LSB until the belt is the correct length, and note the adjusted size of the belt (G).



USING THE LINEMEN'S SIZING BELT



## TO FIND YOUR D-RING SIZE USING A TAPE MEASURE

1. Locate the point where the heel of the hip D-Ring should rest (C).
2. Begin to measure from this point. Measure with a seamstress tape around the buttocks to the same point on the opposite side (D).



USING A TAPE MEASURE

## BELT ADJUSTMENT IN INCHES - PER ASTM F887

D Size - In.	Minimum	Center Hole	Maximum	Tool Loops
D18	32	36	40	3
D19	33	37	41	3
D20	34	38	42	3
D21	36	40	44	4
D22	37	41	45	4
D23	38	42	46	4
D24	40	44	48	4
D25	41	45	49	4
D26	42	46	50	4
D27	44	48	52	4
D28	45	49	53	4

## HIP-GRIP SIZING CHART

Upper Tongue Adj.		Upper Tongue Adj.		Upper Tongue Adj.	
D18	33"-39"	D23 or 24	39"-45"	D27 or 28	43"-49"
D19 or 20	35"-41"	D25 or 26	41"-47"	D29 or 30	45"-51"
D21 or 22	37"-43"				

## REST-A-BACK SIZING CHART

Upper Tongue Adj.		Upper Tongue Adj.		Upper Tongue Adj.	
D18	29"-36"	D23	34"-41"	D27	38"-45"
D19	30"-37"	D24	35"-42"	D28	39"-46"
D20	31"-38"	D25	36"-43"	D29	40"-47"
D21	32"-39"	D26	37"-44"	D30	41"-48"
D22	33"-40"				

# FEATURES OF BASHLIN BELTS

## S-SHAPED D-RINGS:

This is Bashlin's original design. The toe lies away from the belt for easier snap engagement, while the curve reduces pressure on the hip for comfort.

## ALL LEATHER CUSHION SECTION:

The glove soft, rolled edge cushion provides for a belt which is cooler in the summer, yet flexible in cold weather.

## TOP QUALITY MATERIAL:

We utilize the highest quality hardware, nylons, and leathers available.

## BASHLIN CRAFTSMANSHIP:

Years of quality manufacturing are built into each product for a subtle, yet meaningful difference. We encourage side by side comparison.

# BASHLIN TOOL BELT STYLES

## 4 D-RING TOOL BELTS:



88MX4D

### STACKED 4 D-RING



884D

### IN-LINE 4 D-RING



88BMX

### HIP-GRIP/REST-A-BACK 4 D-RING



1515PX

### STACKED FIXED 4 D-RING

## 2 D-RING TOOL BELTS:



1511N

### STANDARD - FIXED 2 D-RING



88

### SEMI-FLOATING - SHIFTING 2 D-RING

## ! STANDARD EQUIPMENT ON BASHLIN BELTS INCLUDES:

4 D-Rings for gut strap attachment (exception - Hip-Grip and Rest-A-Back belts), tape sling, knife snap, glove bag ring and 2 hammer loops and 4 tool loops.

**NOTE:** D18, D19, and D20 tool belts have 3 tool loops due to the shorter belt section.

Bashlin 4 D-Ring Body Belts are patented under PAT 9.737.737 and 10.099.073

## ! MADE TO ORDER BELTS

All "Made to Order" belts are manufactured outside of standard production. Once the order is placed, it cannot be cancelled. Please allow additional shipping time for all made to order belts.

## ! STOCK AND SPECIAL BELTS

Bashlin offers right handed belts, in sizes D18 to D28 of the most popular belts. Belt sizes may vary on different style belts. Larger belts, up to D32, may be ordered. There is an additional cost for sizes D29 to D32.

Belts and holsters with left hand design are available at no additional cost. Add "LH" to the part number.

# 4 D-RING TOOL BELTS



88UX4DMP

## EZRIDER

- Like working in a "Rocking Chair".
- Saddle design relieves hip and leg pressure.
- Worn slightly higher than a standard tool belt.
- Semi-Float with shifting upper D-Rings fixed lower D-Rings.

<b>No. 88UX4DMP</b>	Nylon mesh cushion	Wt. 6.5 lb.
<b>No. 88UX4DCC</b>	Leather comfort cushion	Wt. 7.0 lb.



1515PX4D

## EZRIDER LITE

- Our lightest 4 D-Ring belt.
- Nylon or leather cushion.
- Fixed 4 D-Ring.

<b>No. 1515PX4D</b>	Nylon cushion	Wt. 4.6 lb.
<b>No. 1515PX4DCC</b>	leather comfort cushion	Wt. 4.8 lb.
<b>No. 1515PX</b>	Nylon cushion with two steel upper D-Rings and nylon loop lower	Wt. 4.5 lb.



**WARNING:** Never carry wire, tools, or anything other than the "positioning" strap in the D-Rings of a tool belt. Foreign objects carried in the D-Rings may cause the snap to malfunction and accidental disengagement to occur.



## Labrador

- 7" wide for support.
- Made in nylon mesh or soft leather cushion.
- 3 different design choices for different needs.
- Semi-Float with shifting lower D-Rings and fixed upper D-Rings.



Q88GX4DMP

### LABRADOR "AMIGO"

- Easy donning quick release buckle upper.
- Tongue and buckle lower.
- Easy to adjust nylon webbing.

<b>No. Q88GX4DMP</b>	Nylon mesh cushion	Wt. 5.5 lb.
<b>No. Q88GX4DCC</b>	Leather comfort cushion	Wt. 6.0 lb.



88GX4DCC

### LABRADOR "YUKON"

- Dependable double tongue design.
- Leather faced nylon billet.

<b>No. 88GX4DMP</b>	Nylon mesh cushion	Wt. 6.0 lb.
<b>No. 88GX4DCC</b>	Leather comfort cushion	Wt. 6.5 lb.



88MX4DMP

### LABRADOR "LIBERTY"

- The freedom of a single tongue.
- Durable 7" back.

<b>No. 88MX4DMP</b>	Nylon mesh cushion	Wt. 5.0 lb.
<b>No. 88MX4DCC</b>	Leather comfort cushion	Wt. 5.5 lb.



# 4 D-RING TOOL BELTS



88BMX4DCC

## BMX SERIES



- Modeled after Bashlin's Rest-A-Back and Hip Grip, this proven design offers excellent support.
- Double tongue and buckle design.
- Semi-Float with shifting lower D-Rings and fixed upper D-Rings.

<b>No. 88BMX4DMP</b>	Nylon mesh cushion	Wt. 7.0 lb.
<b>No. 88BMX4DCC</b>	Leather comfort cushion	Wt. 7.0 lb.
<b>No. 88BMX4D</b>	Durable leather back	Wt. 7.0 lb.



Q88BMX4DCC

## BMX QR SERIES



- Modeled after Bashlin's Rest-A-Back and Hip Grip, this proven design offers excellent support.
- Quick release buckles upper tongue.
- Semi-Float with shifting lower D-Rings and fixed upper D-Rings.

<b>No. Q88BMX4DMP</b>	Nylon mesh cushion	Wt. 7.0 lb.
<b>No. Q88BMX4DCC</b>	Leather comfort cushion	Wt. 7.0 lb.
<b>No. Q88BMX4D</b>	Durable leather back	Wt. 7.0 lb.



88X4D

## FLORIDIAN 4D IN-LINE



- 4 D-Ring version to our traditional 88 Floridian belt.
- Semi-Float design and four shifting D-Rings.
- Leather Comfort Cushion.

<b>No. 884D</b>	Floridian 4D - brown	Wt. 6.5 lb.
<b>No. 88X4D</b>	Floridian 4D - black	Wt. 6.5 lb.



88BSX4DCC

## REST-A-BACK 4D



- Semi-Float with shifting lower D-Rings with fixed upper D-Rings.

<b>No. 88BSX4DCC</b>	Leather comfort cushion	Wt. 9.0 lb.
----------------------	-------------------------	-------------

\*See page 6 for sizing.



88BIX4DCC

## HIP GRIP 4D



- Pliable and removable 1 3/4" upper tongue.
- Contour back for additional comfort.
- Semi-Float with shifting in-line D-Rings.

<b>No. 88BIX4DCC</b>	Hip Grip 4D	
	Leather comfort cushion	Wt.. 9.0 lb.

\*See page 6 for sizing.



**WARNING:** All Bashlin's tool belts are to be worn snug as possible with the large D-Rings and billet on or above the hips. Wearing the belts improperly may cause accidents or death.

## 2 D-RING TOOL BELTS



88

### FLORIDIAN



- The industry standard for over 50 years.
- The original laced belt.
- Flared cushion for easier climbing.
- Semi-Floating with shifting D-Rings.

No. 88

Leather comfort cushion

Wt: 6.5 lb.

No. 88X

Black - leather  
comfort cushion

Wt: 6.5 lb.



160N

### NYLON DELUXE



- Semi-Floating with shifting D-Rings.
- Light and durable nylon back.
- Comfortable leather cushion.
- Tongue and buckle is 6 ply nylon.
- Leather tool loops.

No. 160N

Leather comfort cushion

Wt: 6.0 lb.



1511N

### WRANGLER



- Fixed D-Rings and shifting billet.
- Neoprene nylon back and tongue.
- Lightweight.

No. 1511N

Tool belt

Wt: 5.25 lb.



656PX

### 656 SERIES



- Fixed D-Ring style.
- Lightweight and versatile.
- Moisture wicking mesh pad.

No. 656PX

Black

Wt: 4.0 lb.

No. 656CM

Brown

Wt: 4.0 lb.



**WARNING:** Never carry wire, tools, or anything other than the "positioning" strap in the D-Rings of a tool belt. Foreign objects carried in the D-Rings may cause the snap to malfunction and accidental disengagement to occur.

# AUXILIARY POSITIONING AND SUPPORT BELTS



## LABRADOR APB



- Easily convert your comfortable 2 D-Ring belt to a 4 D-Ring design.
- Quick release attachment straps.
- Fixed D-Rings for easy secondary lanyard connections.
- FR Arc resistant nylon fabric.

<b>No. Q83H2D</b>	Labrador "Tucson"; quick release belt	Wt. 3.0 lb.
<b>No. 83H2D</b>	Labrador "Sierra"; billet style belt	Wt. 3.2 lb.



## LABRADOR "LOBO"



- Orthopedically correct Back-A-Line support belt.
- Fixed D-Rings for easy secondary lanyard connections.

<b>No. 83BDH</b>	Back-A-Line belt	Wt. 3.4 lb.
------------------	------------------	-------------

**SIZING:** Add 4"-6" to the waist measurement  
Small 32"-40" Medium 36"-44" Large 40"-48" X-Large 42"-50"



**WARNING:** Bashlin's Lineman's Belt Supporters are never to be used with a Lineman's belt to create a "saddle". The lineman's belt always must be worn snugly, on or above the hips. Incorrect use may cause accidents or death.



## NYLON WEB SUSPENDERS



- Nylon web suspenders.
- Fully adjustable design (one size fits most).
- Tool belt not included\*.

<b>No. 80HDS</b>	Nylon web suspenders	Wt. 2.75 lb.
------------------	----------------------	--------------



## BELT SUPPORTER STRAP



- Distributes weight of belt and tools.
- Made from top quality russet leather.
- Four adjustable drop straps.

<b>No. 81</b>	Supporter strap	Wt. 1.5 lb.
<b>No. 81-1</b>	Leather drop strap only	Wt. 0.25 lb.



## SAM BROWN SUSPENDERS



- Leather suspenders.

<b>No. 80</b>	Brown	Wt. 1.25 lb.
<b>No. 80X</b>	Black	Wt. 1.25 lb.



**NOT A SAFETY BELT**

# BOLT AND NUT BAGS

## 25A

8 1/2" x 9" x 4" bolt and nut bag with a reinforced top to stay open.

- No corners to lose hardware.
- Features an inside pocket.
- Secures to a belt with two straps joined by snaps and D-Rings.
- Available in traditional canvas, black ballistic nylon, orange nylon, and camo nylon.



**No. 25A**

Canvas bag with straps

Wt: 0.7 lb.



**No. 25ABX**

Black ballistic nylon bag with straps

Wt: 0.7 lb.



**No. 25A-0**

Orange nylon bag with straps

Wt: 0.7 lb.



**No. 25A-C**

Camo nylon bag with straps

Wt: 0.7 lb.

## 25AM2 WITH MAGNET

Similar to the popular 25A with the addition of 3 inner tool loops, inside pocket and a strong magnet to hold onto hardware such as nuts and cotter keys.



**No. 25AM2**

Canvas bag with magnet

Wt: 1.0 lb.



**No. 25AM2BX**

Black ballistic nylon bag with magnet

Wt: 1.0 lb.



**No. 25AM2-0**

Orange nylon bag with magnet

Wt: 1.0 lb.



**No. 25AM2-C**

Camo nylon bag with magnet

Wt: 1.0 lb.



# BOLT AND NUT BAGS



## 26DRM

- All leather pouch with tool holders inside.

**No. 26DRM** 9" x 9" x 2 1/2"

Wt: 0.5 lb.



## 25BS

- Canvas with snap or thong attachment.

**No. 25BS** 8" x 9" x 2 1/2"

Wt: 0.5 lb.



## 25PLS

- An all leather bag with reinforced top.
- Snap or leather thong attachment.

**No. 25PLS** 8" x 9" x 3"

Wt: 0.9 lb.



## 25KLBS

- Durable leather with snap or thong attachment.

**No. 25KLBS** 8" x 9" x 2 1/2"

Wt: 0.8 lb.



## 25PS

- Wide opening canvas bag with leather bottom and snap attachment.

**No. 25PS** 8" x 8" x 2 1/2"

Wt: 0.6 lb.



26L

26LX

## 26L

- Very heavy, durable leather.
- Features a double top to stay open.
- Leather thong attachment.

**No. 26L** 9" x 9" x 2 1/2"

Wt: 0.7 lb.

**No. 26LX** 9" x 9" x 2 1/2"

Wt: 0.7 lb.



## 25R

- Cotton duck bag with 1" straps and leather ties.
- Reinforced top to keep open.

**No. 25R** 8" x 8 1/2" x 4"

Wt: 0.5 lb.



## 26G

- A soft leather bag with snap closure and leather thongs.

**No. 26G** 8 1/2" x 9"

Wt: 0.5 lb.

# LINEMEN'S HOLSTERS

Bashlin manufactures only premium holsters for tool belts. They feature double harness leather backs reinforced for extra wear. All holsters come with the hardware necessary for proper attachment.



111HS



111HSX

## 3 POCKET HOLSTER

- No. 111HS** For pliers, rule, screwdriver, and knife or wrench Wt: 1.0 lb.
- No. 111HSX** For pliers, rule, screwdriver, and knife or wrench - black Wt: 1.0 lb.



111HLS



111HLSX

## 4 POCKET HOLSTER

- No. 111HLS** For pliers, rule, screwdriver, Channellock®, and knife or wrench Wt: 1.25 lb.
- No. 111HLSX** For pliers, rule, screwdriver, Channellock®, and knife or wrench - black Wt: 1.25 lb.



111HLDS



111HLDSX

## 5 POCKET HOLSTER

- No. 111HLDS** For pliers, rule, screwdriver, Channellock®, ratchet driver, and knife or wrench Wt: 1.5 lb.
- No. 111HLDSX** For pliers, rule, screwdriver, Channellock®, ratchet driver, and knife or wrench - black Wt: 1.5 lb.



111HE



111HEX

## 3 POCKET HOLSTER AND KNIFE SHEATH

- No. 111HE** For pliers, rule, screwdriver, and knife Wt: 1.25 lb.
- No. 111HEX** For pliers, rule, screwdriver, and knife - black Wt: 1.25 lb.



111HLE



111HLEX

## 4 POCKET HOLSTER AND KNIFE SHEATH

- No. 111HLE** For pliers, screwdriver, Channellock®, rule, and knife Wt: 1.5 lb.
- No. 111HLEX** For pliers, screwdriver, Channellock®, rule and knife - black Wt: 1.5 lb.



111HLDSE



111HLDSEX

## 5 POCKET HOLSTER AND KNIFE SHEATH

- No. 111HLDSE** For pliers, rule, screwdriver, Channellock®, ratchet driver, and knife or wrench Wt: 1.75 lb.
- No. 111HLDSEX** For pliers, rule, screwdriver, Channellock®, ratchet driver, and knife or wrench - black Wt: 1.75 lb.

# LINEMEN'S HOLSTERS



111SK



111SKX

## SKINNING KNIFE HOLSTER

**No. 111SK**

Skinning knife holster

Wt: 0.75 lb.

**No. 111SKX**

Skinning knife holster - black

Wt: 0.75 lb.



4HP

## BASHLIN HOLSTER PACK

- Contains two rivet type screws, one small D-Ring, and piece of leather (black or brown) to attach tool holster to belt.

**4HP**

Brown

Wt: 0.1 lb.

**4HPX**

Black

Wt: 0.1 lb.



111BWH



111BWHX

## BELL WRENCH HOLDER

**No. 111BWH**

For bell wrenches

Wt: 0.6 lb.

**No. 111BWHX**

For bell wrenches - black

Wt: 0.6 lb.



4STR

## 4 SCREW TYPE RIVETS TO SECURE HOLSTER TO BELT

**4STR**

Screw type rivets

Wt: 0.05 lb.



111LWH



111LWHX

## LOWELL WRENCH HOLDER

**No. 111LWH**

For the Lowell wrench

Wt: 0.6 lb.

**No. 111LWHX**

For the Lowell wrench - black

Wt: 0.6 lb.



Left handed holsters are available at no extra cost.  
(Add an "-LH" to the part number when ordering.)

# GROUNDMAN HOLSTER ACCESSORIES - CARE



112HLS



112HLSX

## GROUNDMEN'S HOLSTER

Bashlin's single backed groundmen's holster is slotted for easy attachment. It features the same pliable pockets used on our linemen's holsters. Do not use these holsters on linemen's tool belts.

**No. 112HLS** For pliers, rule, screwdriver, knife, Channellock® or wrench Wt: 1.0 lb.

**No. 112HLSX** For pliers, rule, screwdriver, knife, Channellock® or wrench - black Wt: 1.0 lb.



**WARNING:** Do not use groundmen's or electrician's holsters on linemen's tool belts.



33




33L

## HANDLINE CARRIER

The nylon handline carrier fits over the tongue-buckle section of the belt. It is designed to straighten and drop the rope if the handline becomes snagged. The 33L locks on the belt.

**No. 33** Handline carrier Wt: 0.1 lb.

**No. 33L** Handline carrier with lock Wt: 0.1 lb.



31L

31R

## TAPE SLINGS

These swivel bar tape slings will fit any size tape roll. For black - add "X" to part number.

<b>No. 31L</b>	Loop type	Wt: 0.1 lb.
<b>No. 31R</b>	Rivet type	Wt: 0.1 lb.



32A

32AR

32B

32BR

## LOOP-N-SNAP

These convenient extra snaps will fit 2" belts. For black - add "X" to part number.

<b>No. 32A</b>	Small snap for knives	Wt: 0.2 lb.
<b>No. 32AR</b>	Small snap with screw rivets	Wt: 0.2 lb.
<b>No. 32B</b>	Large snap for wrenches	Wt: 0.3 lb.
<b>No. 32BR</b>	Large snap with screw rivets	Wt: 0.3 lb.

806-32

806-16

806-8



804

809

## LEATHER MAINTENANCE PRODUCTS

Long life for your leather products begins with proper care. Use Saddle Soap to clean the dirt out of the leather, then coat the leather to protect them with "Neatsfoot" or Mink Oil.

<b>No. 804</b>	Saddle Soap	Wt: .75 lb.
<b>No. 806-8</b>	Neatsfoot Oil (8 oz.)	Wt: .50 lb.
<b>No. 806-16</b>	Neatsfoot Oil (16 oz.)	Wt: 1.0 lb.
<b>No. 806-32</b>	Neatsfoot Oil (32 oz.)	Wt: 2.0 lb.
<b>No. 809</b>	Mink Oil	Wt: .30 lb.





# ALUMINUM CLIMBERS **RETOOLED**

- ◆ **NEW, INNOVATIVE PROFILE FOR ENHANCED DURABILITY**
- ◆ *SAME TRIED AND TRUE CLIMBING FEEL*
- ◆ **SAME PROVEN AND EFFECTIVE REPLACEABLE GAFF, GAFF ANGLE AND POSITION**



Natural Aluminum  
BD14B



Black Anodized  
BD14BX



OD Green Anodized  
BD14BOD

**Forged and Manufactured in USA**  
**from 2014-T6 Aluminum Alloy**  
Offered in 3 High Quality Finishes

# POLE CLIMBERS


## BD14B ALUMINUM

- Lightweight aluminum climber.
- Features replaceable gaffs.
- Weighs the same as comparable titanium climbers.
- Offset design gives great climbing qualities.

<b>No. BD14B-1N</b>	Aluminum alloy with bottom straps	Wt: 3.5 lb.
<b>No. BD14B-2N</b>	Bottom straps and top straps	Wt: 4.75 lb.
<b>No. BD14B-3N</b>	Bottom straps, top straps and #110D pads	Wt: 5.25 lb.



Natural Aluminum  
BD14B



Black Anodized  
BD14BX



OD Green Anodized  
BD14BOD

<b>No. BD14B-4N</b>	Bottom straps, top straps and #130D pads	Wt: 5.50 lb.
<b>No. BD14B-5N</b>	Bottom straps, top straps and #140DS pads	Wt: 5.75 lb.
<b>No. BD14BP-1N</b>	For CCA poles - polished gaffs	Wt: 3.5 lb.
<b>No. BD14BA-1N</b>	Longer top slide (18"-21")	Wt: 3.5 lb.

## BD16B STEEL

- Durable steel alloy climber.
- Features replaceable gaffs.
- Extra ankle room for linemen who have trouble with rubbing in that area.
- Offset design gives great climbing qualities.




BD16B

<b>No. BD16B-1N</b>	Steel alloy, straight shanks with bottom straps	Wt: 5.0 lb.
<b>No. BD16B-2N</b>	Bottom straps and top straps	Wt: 6.0 lb.
<b>No. BD16B-3N</b>	Bottom straps and #110D pads	Wt: 6.5 lb.
<b>No. BD16B-4N</b>	Bottom straps, top straps and #130D pads	Wt: 6.75 lb.

<b>No. BD16B-5N</b>	Bottom straps, top straps and #140DS pads	Wt: 7.0 lb.
<b>No. BD16BP-1N</b>	For CCA poles - polished gaffs	Wt: 5.0 lb.
<b>No. BD16BA-1N</b>	Longer top slide (18"-21")	Wt: 5.0 lb.

## BD16BC TWISTED SHANK STEEL

- Our most popular steel alloy climber.
- Features replaceable gaffs.
- Has a 3° twisted shank so the climber lays flat against the leg.
- Extra ankle room like the BD16B.



BD16BC

<b>No. BD16BC-1N</b>	Steel alloy, twisted shank with bottom straps	Wt: 5.0 lb.
<b>No. BD16BC-2N</b>	Bottom straps and top straps	Wt: 6.0 lb.
<b>No. BD16BC-3N</b>	Bottom straps, top straps and #110D pads	Wt: 6.5 lb.

<b>No. BD16BC-4N</b>	Bottom straps, top straps and #130D pads	Wt: 7.0 lb.
<b>No. BD16BC-5N</b>	Bottom straps, top straps and #140DS pads	Wt: 7.0 lb.
<b>No. BD16BCP-1N</b>	For CCA poles - polished gaffs	Wt: 5.0 lb.
<b>No. BD16BCA-1N</b>	Longer top slide (18"-21")	Wt: 5.0 lb.



All Bashlin Climbers feature Bashlin's superior performing 17° gaff. Gaff Guards and a Gaff Gauge are included with Bashlin Climbers. The standard top slide length has an adjustment of 15"-18". There are longer top slides available, with an adjustment of 18"-21" (A).

# POLE CLIMBERS

## BD12 STEEL

- Lightweight, steel alloy climber.
- Features riveted non-replaceable gaffs.
- Excellent climbing characteristics.
- Offset design places gaff in proper position for easier penetration.



BD12

<b>No. BD12-1N</b>	Steel alloy with bottom straps	Wt: 5.0 lb.	<b>No. BD12-4N</b>	Bottom straps, top straps and #130D pads	Wt: 6.25 lb.
<b>No. BD12-2N</b>	Bottom straps and top straps	Wt: 5.5 lb.	<b>No. BD12-5N</b>	Bottom straps, top straps and #140DS pads	Wt: 6.5 lb.
<b>No. BD12-3N</b>	Bottom straps, top straps and #110D pads	Wt: 6.0 lb.	<b>No. BD12P-1N</b>	For CCA poles - polished gaffs	Wt: 5.0 lb.
			<b>No. BD12A-1N</b>	Longer top slide (18"-21")	Wt: 5.0 lb.

## BD12C TWISTED SHANK STEEL

- This steel alloy climber is an excellent value.
- Features a riveted non-replaceable gaff.
- Has a 3° twisted shank so the climbers lay flat against the leg.
- Offset design places gaff in proper position for easier penetration.




BD12C

<b>No. BD12C-1N</b>	Steel alloy, twisted shank with bottom straps	Wt: 5.0 lb.	<b>No. BD12C-4N</b>	Bottom straps, top straps and #130D pads	Wt: 6.25 lb.
<b>No. BD12C-2N</b>	Bottom straps and top straps	Wt: 5.5 lb.	<b>No. BD12C-5N</b>	Bottom straps, top straps and #140DS pads	Wt: 6.5 lb.
<b>No. BD12C-3N</b>	Bottom straps, top straps and #110D pads	Wt: 6.0 lb.	<b>No. BD12CP-1N</b>	For CCA poles - polished gaffs	Wt: 5.0 lb.
			<b>No. BD12CA-1N</b>	Longer top slide (18"-21")	Wt: 5.0 lb.

## BD12L STEEL

- Steel alloy climber.
- Features a riveted non-replaceable gaff.
- Has a narrower stirrup, it measures 3 3/4", the standard measurement is 4 3/4".
- Offset design places gaff in proper position for easier penetration.



BD12L

<b>No. BD12L-1N</b>	Steel alloy, narrow stirrup with bottom straps	Wt: 5.0 lb.	<b>No. BD12L-4N</b>	Bottom straps, top straps and #130D pads	Wt: 6.25 lb.
<b>No. BD12L-2N</b>	Bottom straps and top straps	Wt: 5.5 lb.	<b>No. BD12L-5N</b>	Bottom straps, top straps and #140DS pads	Wt: 6.5 lb.
<b>No. BD12L-3N</b>	Bottom straps, top straps and #110D pads	Wt: 6.0 lb.	<b>No. BD12LP-1N</b>	For CCA poles - polished gaffs	Wt: 5.0 lb.
			<b>No. BD12LA-1N</b>	Longer top slide (18"-21")	Wt: 5.0 lb.



Bashlin tree climbers also available. Contact customer service for more information.

# CLIMBER PADS



## SPUR-STAY CLIMBER PADS

Developed by a local lineman over 50 years ago, Bashlin introduced the 105 series "Spur-Stay" climber pads with metal inserts for the lineman looking for comfort and shank control. Some of the original users were mocked for using these pads because comfort was not considered "manly". (This is when a climber pad was a single piece of leather measuring 3" x 3".)

The Spur-Stay design allows the climber to adjust the position of the shank, and eliminates "kick-back". It is available with straps or Hook-N-Loop closures.



145BCV



145AC

145BC

## 145ACV/145BCV/145FCV

This Hook-N-Loop cinch closure pad has deep padding, moisture wicking mesh, and an angled metal insert.

<b>No. 145ACV</b>	For BD16B series and BD12 series climbers	Wt. 4.1 lb.
<b>No. 145BCV</b>	For BD14 climbers	Wt. 4.1 lb.
<b>No. 145FCV</b>	For BD14B climbers	Wt. 4.1 lb.

## 145AC/145BC/145FC

This Durable Leather "wide" climber pad has moisture wicking padding, metal insert and a pair of top climber straps.

**\*\* 1 pair of straps is included with pads \*\***

<b>No. 145AC</b>	For BD16B series and BD12 series climbers	Wt. 3.3 lb.
<b>No. 145BC</b>	For BD14 climbers	Wt. 3.3 lb.
<b>No. 145FC</b>	For BD14B climbers	Wt. 3.3 lb.



145BCVW



105BC

## 145ACVW/145BCVW/145FCVW

This "wide" pad combines the Hook-N-Loop cinch closure pad combined with sturdy leathers, moisture wicking padding, and angled metal inserts to provide added comfort.

<b>No. 145ACVW</b>	For BD16B series and BD12 series climbers	Wt. 3.5 lb.
<b>No. 145BCVW</b>	For BD14 climbers	Wt. 3.5 lb.
<b>No. 145FCVW</b>	For BD14B climbers	Wt. 3.5 lb.

## 105AC/105BC/105FC

This is the original Spur-Stay design. It is lightweight, yet provides comfort and total climber control.

<b>No. 105AC</b>	For BD16B series and BD12 series climbers	Wt. 1.5 lb.
<b>No. 105BC</b>	For BD14 climbers	Wt. 1.5 lb.
<b>No. 105FC</b>	For BD14B climbers	Wt. 1.5 lb.



Replacement Irons add "R" to the above part numbers. Sold in pairs.



For climber pads with "straight" metal inserts drop "C" from above part number.



# CLIMBER PADS




150V

## 150V - HOOK-N-LOOP PADS

- Constructed from woven nylon with a soft padding sewn inside.
- Hook-N-Loop closure for extra security.
- Leather tunnel loop to keep the pad in place on the climber.
- Slight angle for an improved gaff position.

**No. 150V** Hook-N-Loop with "T" design Wt: 4.0 lb.



150TS

## 150T SERIES

- "T" pad constructed from durable latigo leather.
- Offers comfort and protection for the shin and calf.
- Leather lugs are securely riveted for long wear.
- Shank area is available with or without padding.

**No. 150T** Not padded Wt: .8 lb.  
**No. 150TS** Padded Wt: .9 lb.



110D

## 110D SERIES

- Basic 2 ply universal fit leather pad that will protect the calf and shin.

**No. 110D** Not padded Wt: 0.6 lb.  
**No. 110DS** Padded Wt: 0.7 lb.



130D

## 130D

- Bashlin's original "L" pad.
- Constructed from durable latigo leather.
- Light padding for comfort, while still keeping the pad lightweight.
- Allows shank movement for linemen that prefer less restriction.

**No. 130D** Padded Wt: 0.7 lb.



140DS

## 140D SERIES

- Constructed from durable latigo leather.
- Wing design holds the shank securely, and at a slight angle for enhanced control.
- Climber shank fits inside the pad, to add comfort while reducing movement.
- The shank area is available with or without padding.

**No. 140D** Not padded Wt: 0.8 lb.  
**No. 140DS** Padded Wt: 1.25 lb.

# CLIMBER PARTS AND ACCESSORIES



85N - 24"



86N - 28"



87N - 28"



89N - 28"

## CLIMBER STRAPS

- Constructed from durable, pliable, and comfortable neoprene nylon (N) or flexible "Bioplastic" coated webbing (NP).
- Double riveted and feature a protective buckle shield.

<b>No. 85N</b>	1 1/16"x24"	
	top climber straps	Wt: 0.6 lb.
<b>No. 85NP</b>	1 1/16"x24"	
	top climber straps	Wt: 0.6 lb.
<b>No. 86N</b>	1 1/16"x28"	
	top climber straps	Wt: 0.6 lb.
<b>No. 86NP</b>	1 1/16"x28"	
	top climber straps	Wt: 0.6 lb.
<b>No. 87N</b>	1 1/16"x28" two piece	
	bottom straps	Wt: 0.7 lb.
<b>No. 87NP</b>	1 1/16"x28" two piece	
	bottom straps	Wt: 0.7 lb.
<b>No. 89N</b>	1 1/16"x28" two piece split ring	
	bottom straps	Wt: 0.7 lb.
<b>No. 89NP</b>	1 1/16"x28" two piece split ring	
	bottom straps	Wt: 0.7 lb.



14TS



14ATS



16TS



16ATS

## TOP SLIDES (screws are included)

- Fits all Bashlin climbers.
- The standard adjustment is 15"-18".
- There are longer top slides available, with an adjustment of 18"-21".
- Order according to your climbers.

<b>No. 14TS</b>	For BD14, 15"-18" adjustment	Wt: 0.6 lb.
<b>No. 14ATS</b>	For BD14, 18"-21" adjustment	Wt: 0.85 lb.
<b>No. 14TSB</b>	For BD14B, 15"-21" adjustment	Wt: 0.6 lb.
<b>No. 14ATSB</b>	For BD14B, 18"-21" adjustment	Wt: 0.85 lb.
<b>No. 16TS</b>	For BD16B, BD12 series, 15"-18" adjustment	Wt: 0.6 lb.
<b>No. 16ATS</b>	For BD16B, BD12 series, 18"-21" adjustment	Wt: 0.85 lb.



3

## CLIMBER STRAP SPLIT RING

<b>No. 3</b>	Split ring for climber straps (package of 2)	Wt: 0.15 lb.
--------------	--	--------------



4G



4T

## SCREWS

- Screws are small and easy to lose.
- Bashlin offers replacement screws for gaffs and top slides.

<b>No. 4G</b>	Gaff screws	Wt: .05 lb.
<b>No. 4T</b>	Slide adjustor screws	Wt: .05 lb.

# CLIMBER PARTS AND ACCESSORIES



14

14P

14T

## REPLACEMENT GAFFS

- Fits the BD14, BD14B, BD16B, and BD16BC climbers.
- The standard 14 gaff is 1 5/8" long.
- The 14P gaff is 1 5/8" and had the machine marks removed for easier penetration on hard/CCA poles.
- The 14T gaff is 2 1/2" long to penetrate thick bark.

<b>No. 14</b>	1 5/8" pole gaffs with screws	Wt: 0.5 lb.
<b>No. 14P</b>	1 5/8" polished pole gaffs with screws	Wt: 0.5 lb.
<b>No. 14T</b>	2 1/2" tree gaffs with screws	Wt: 0.6 lb.

\*Only Bashlin Replacement Gaffs may be used on Bashlin Climbers.



27

## GAFF SHAPING KIT

- Nice compact design.
- Contains all of the tools needed to properly care for the gaffs on your Bashlin climbers.
- Includes #5 gaff gauge, 6" mill file with wooden handle, sharpening stone, and instructions.
- For use with Bashlin pole gaffs only.

<b>No. 27</b>	Gaff shaping kit	Wt: 0.55 lb.
---------------	------------------	--------------



5

## GAFF GAUGE

- For use with Bashlin pole climbers only.
- Used to maintain the correct shape, taper, and profile of your gaffs.
- Shaping instructions are included.

<b>No. 5</b>	Gaff gauge	Wt: 0.2 lb.
--------------	------------	-------------



2

2SC

B1972G

B1972F

## GAFF GUARDS

- Helps keep the gaff protected.
- Helps to protect the user from scratches and puncture wounds.
- Sold in pairs.

<b>No. 2</b>	Standard leather guard with Hook-N-Loop	Wt: 0.2 lb.
<b>No. 2SC</b>	Deluxe leather guard with Hook-N-Loop attachment	Wt: 0.25 lb.
<b>No. B1972G</b>	Snap on guard for replaceable gaffs	Wt: 0.2 lb.
<b>No. B1972F</b>	Snap on guard for fixed gaffs	Wt: 0.2 lb.




BHP

## HEEL COVER

- Wearing a pair of climbers exposes the lineman's ankle and Achilles tendon to injury.
- Covers this vulnerable area, while not restricting any movement.
- They are light, durable, and easily attach to any standard climber.

<b>No. BHP</b>	One size fits most, sold as pair	Wt: .5 lb.
----------------	----------------------------------	------------

# FALL RESTRICTING DEVICE



## THE PATRIOT™

New and unique design that frees the lineman from the "Tyranny and Restriction" of other fall restraint products.

- Easy, natural movement up and down the pole.
- Light weight - over 20% lighter than other devices.
- Easy movement and light weight=less fatigue for the climber.
- Rope rollers allow freedom of movement left and right while working.
- Easily adapts for left and right handed climbers.

<b>No. 76PAT</b>	6" - 20" diameter poles	Wt: 3.5 lb.
<b>No. 76PAT-T</b>	6" - 30" diameter poles	Wt: 3.5 lb.

## REPLACEMENT PARTS

<b>No. 76PAT-ORC</b>	Includes replacement pole rope and rope clamp	Wt: 1.0 lb.
<b>No. 76PAT-OR</b>	Includes replacement rope	Wt: .75 lb.

\*The Patriot meets ASTM F887 Type A/B requirements. Including icy or slippery poles.

**AN INSTRUCTIONAL VIDEO IS ON OUR WEBSITE OR WWW.BASHLINPATRIOT.COM**

HARDENED INNER ROPE ROLLERS ARE DURABLE AND ALLOW GREATER MOBILITY ON THE POLE.

NEW ROPE CLAMP ALLOWS POLE ROPE REPLACEMENT IN THE FIELD.

## AS A RESULT OF INDEPENDENT TESTING THE PATRIOT HAS BEEN CLASSIFIED AS "ERGONOMIST APPROVED".

It's 3.5 lb. weight is less than the 4lb. weight threshold determined by ergonomist studies to cause damaging repetitive motion strains.

The Patriot reduces stress on the arms and shoulders and potential repetitive strain injuries caused by climbing with other Fall Restraint Devices.



**WARNING:** The carabiners, connector slot and connector latch should be free from debris, open easily and close completely. Verify all connections. The rope clamp should have no signs of stress, no loose screws, nor indicate movement of the line. The red wear indicators of the black outer line, or the red/white/blue inner line should not be visible. If your Patriot has any of these discrepancies, it must be removed from service.



# POLE STRAPS



51N-2HL

## 50 SERIES



The 6 ply 1 3/4" neoprene coated nylon material uses a tongue buckle adjustment, and has a red wear indicator.

Part No.	Length		Wt:
<b>No. 51N-2HL</b>	5'6"	Pole strap	3.75 lb.
<b>No. 52N-2HL</b>	6'	Pole strap	3.75 lb.
<b>No. 53N-2HL</b>	6'6"	Pole strap	4.0 lb.
<b>No. 54N-2HL</b>	7'	Pole strap	4.0 lb.



78A-2HL

## 78 SERIES



Bashlin's pliable latigo leather straps feature a nylon insert. The stitching is deeply embedded in the leather for longer wear.

Part No.	Length		Wt:
<b>No. 78X-2HL</b>	5'6"	Pole strap	4.25 lb.
<b>No. 78A-2HL</b>	6'	Pole strap	4.25 lb.
<b>No. 78B-2HL</b>	6'6"	Pole strap	4.5 lb.
<b>No. 78C-2HL</b>	7'	Pole strap	4.5 lb.

**WARNING:** Always visually confirm that the snap is on the D-Ring with the gate closed and locked before allowing the strap to support your body weight. Do not just listen for the "click".



47N-15

## EXTENSION STRAPS



Bashlin's extension straps are made from 6 ply nylon and forged steel hardware. The available lengths are 15" and 18".

Part No.	Length		Wt:
<b>No. 47N-15</b>	15"	Extension strap	1.0 lb.
<b>No. 47N-18</b>	18"	Extension strap	1.0 lb.



41NW-2HL

## 40NW SERIES

The orange woven nylon is soft, pliable, and has a red wear indicator in the center. Adjustment is made with a forged steel friction adjuster.

Part No.	Length		Wt:
<b>No. 41NW-2HL</b>	5'6"	Pole strap	3.5 lb.
<b>No. 42NW-2HL</b>	6'	Pole strap	3.5 lb.
<b>No. 43NW-2HL</b>	6'6"	Pole strap	4.0 lb.
<b>No. 44NW-2HL</b>	7'	Pole strap	4.0 lb.

**WARNING:** Double action locking snaphooks reduce, but do not eliminate, the possibility of accidental disengagement. Caution and proper work methods including keeping the Snap/ D-Ring area free from foreign objects must be practiced at all times. Disabling the gate locks may cause accidents, injury, or death.

**WARNING:** The 40 and 50 series straps have red wear indicators in the center to help determine when it is time to replace them.

# ADJUSTABLE ROPE POSITIONING LANYARDS

- Bashlin's Rope Lanyards for transitioning obstacles when climbing or descending poles are available in several materials with multiple wear protection, adjuster, and snap-hook options.
- Twist lock aluminum carabiner is standard on adjusters.
- Rope options (all have red core for inspection).

## YALE BLAZE 16 STRAND XTC

XTC 16 is a tight braid consisting of 16 individual strands of polyester. A high-twist core of torque-balanced polyester keeps the construction firm and round, providing an extra measure of safety. XTC 16 is an excellent choice due to its no snagging, abrasion-resistant construction and excellent energy absorption characteristics.

## UNILINE

Uniline is a parallel-core cable of PET (polyester) filament. The Uniline core is bonded together with a rubber-based adhesive, wrapped with red rubber tape, over-braided with a tough polyester sleeve.

**\*\* NEW \*\***

## NEW "R.I.N.G." ROPE

R.I.N.G Rope is engineered with superior durability and ease of inspection in mind. The modified "TECHNORA" over-braid is designed to maximize cut and abrasion resistance. Inside, you'll find a modified Kernmantle construction. The red polyester sub-sleeve is easily identifiable if the rope becomes compromised due to wear and tear. If the red damage indicator is exposed, just remember - "Red-Is-No-Go!"



### WARNING:

Verify connections and red wear indicator.



## ADJUSTOR CHOICES

- 4016 Style-standard or straight cam
- 4019 Style-90 degree twist cam



## ROPE CONSTRUCTION (ALL HAVE RED CORES FOR INSPECTION)

- Braided rope with PVC cover (NX) (A)
- Braided rope with Ballistic nylon/rope roller (NXBC) (B)
- Durable Yale Uniline (UX) (C)
- Ring rope (TX) (D)



## SNAPHOOKS

- Standard steel (1)
- Steel swivel snaphook (SW) (2)
- Aluminum alloy (AL) (3)

# ADJUSTABLE ROPE POSITIONING LANYARDS



4019NXBC-8



4019UX-8

## 4016 LANYARDS - STANDARD ADJUSTOR



<b>No. 4016NX-8</b>	PVC wear cover	Wt. 1.5 lb.
<b>No. 4016NXBC-8</b>	Ballistic nylon wear cover	Wt. 1.5 lb.
<b>No. 4016UX-8</b>	Uniline	Wt. 1.5 lb.
<b>No. 4016NX-8SW</b>	PVC cover/swivel snap	Wt. 1.6 lb.
<b>No. 4016NXBC-8SW</b>	Ballistic nylon/swivel snap	Wt. 1.6 lb.
<b>No. 4016UX-8SW</b>	Uniline/swivel snap	Wt. 1.6 lb.
<b>No. 4016NX-8AL</b>	PVC/aluminum hook	Wt. 1.4 lb.
<b>No. 4016NXBC-8AL</b>	Ballistic/aluminum hook	Wt. 1.4 lb.
<b>No. 4016UX-8AL</b>	Uniline/aluminum hook	Wt. 1.4 lb.

## 4019 LANYARDS - 90° TWIST



<b>No. 4019NX-8</b>	PVC wear cover	Wt. 1.5 lb.
<b>No. 4019NXBC-8</b>	Ballistic nylon wear cover	Wt. 1.5 lb.
<b>No. 4019UX-8</b>	Uniline	Wt. 1.5 lb.
<b>No. 4019NX-8SW</b>	PVC cover/swivel snap	Wt. 1.6 lb.
<b>No. 4019NXBC-8SW</b>	Ballistic nylon/swivel snap	Wt. 1.6 lb.
<b>No. 4019UX-8SW</b>	Uniline/swivel snap	Wt. 1.6 lb.
<b>No. 4019NX-8AL</b>	PVC/aluminum hook	Wt. 1.4 lb.
<b>No. 4019NXBC-8AL</b>	Ballistic/aluminum hook	Wt. 1.4 lb.
<b>No. 4019UX-8AL</b>	Uniline/aluminum hook	Wt. 1.4 lb.

\*\*\* NEW \*\*\*



## 4018TX-8AL



Constructed with 11.5MM Yale "R.I.N.G" Rope, "RAD" device, and an aluminum snap hook. The abrasion and cut resistance of the "TECHNORA" over-braid eliminates the need for additional wear jackets or PVC covers. The "RAD" (Rope Adjustment Device) features an internal breaking system and spring loaded flip out handle which allows for easy one hand operation.

## 4019TX-8AL



Constructed with 11.5MM Yale "R.I.N.G" Rope, 90° twist stop adjuster and an aluminum snap hook this device will hold up under challenging conditions. The abrasion and cut resistance of the "TECHNORA" over-braid eliminates the need for additional wear jackets or PVC covers.



# HAND TOOLS



## RAUCKMAN'S BUG WRENCHES

**RAUCKMAN**  
Utility Products

- See through port to confirm that the ends are separated.

<b>No. BW221</b>	3/8" - 9/16"	Wt: 0.75 lb.
<b>No. BW2212*</b>	1/2" - 9/16"	Wt: 0.75 lb.
<b>No. BW223</b>	Stamped metal, insulating handle, 9/16" and 3/4"	Wt: 0.75 lb.
<b>No. BW223HD</b>	Heavy-duty, drop-forged, insulating handle, 9/16" and 3/4"	Wt: 0.75 lb.
<b>No. BW2237*</b>	5/8" - 3/4"	Wt: 0.75 lb.
<b>No. BW224*</b>	3/4" - 7/8"	Wt: 0.75 lb.
<b>No. BW244</b>	Heavy-duty, 4-in 1, drop-forged, insulating handle, reversing ratchet, 5/8" and 1/2" - 9/16" and 3/4"	Wt: 0.75 lb.
<b>No. BW288</b>	Heavy-duty, head 1: drop-forged 5/16" hex (Allen) with 2" working length, head 2: ratchet penta socket with built-in 3/8" hex socket for "twist off" lock, insulating handle	Wt: 1.10 lb.
<b>No. BW251</b>	Heavy-duty 4-in 1, drop-forged, insulating handle, reversing ratchet, 5/8" and 1/2" - 9/16" and 3/4"	Wt: .75 lb.
<b>No. R9074</b>	Penta socket with 3/8" drive, deep well	Wt: 0.5 lb.

\*Not shown



3146

## KLEIN "BELL" LINEMEN'S WRENCH

<b>No. 3146</b>	5/8" hardware	Wt: 2.0 lb.
-----------------	---------------	-------------



D507-8

D507-10

D507-12

## KLEIN ADJUSTABLE WRENCHES

- Heavy duty wrenches are made of steel alloy.
- Feature an extra capacity design.
- Plastic dipped handles.

<b>No. D507-8</b>	8" length and 1 1/8" capacity	Wt: 1.0 lb.
<b>No. D507-10</b>	10" length and 1 5/16" capacity	Wt: 1.0 lb.
<b>No. D507-12</b>	12" length and 1 1/2" capacity	Wt: 1.5 lb.



100TDE

101TDE

103TDE

150-12

8D

## LOWELL LINEMEN'S WRENCHES

- Square socket fits 3/4", 1", 1 1/8".
- Hex end fits 9/16", 3/4", and 5/8" square nuts.
- Reversing lever at head.
- Bolt-thru design.

<b>No. 100TDE</b>	8 1/4" ergo grip	Wt: 1.5 lb.
<b>No. 101TDE</b>	9 1/4" steel handle	Wt: 2.0 lb.
<b>No. 103TDE</b>	12 1/4" steel handle	Wt: 2.25 lb.

## TRIPLE SQUARE

- 3/4", 1", 1-1/8"

<b>No. 150-12</b>	12" steel handle	Wt: 2.5 lb.
-------------------	------------------	-------------

## QUAD WRENCH

- 3/4", 13/16", 1", 1 1/8"

<b>No. 8D</b>	12" ergo handle	Wt: 1.5 lb.
---------------	-----------------	-------------

Bashlin sells the complete line of Lowell products.  
Call or write for information.



# HAND TOOLS



D213-9NE



D2000-9NE



D2000-9NETH

## LINEMEN'S PLIERS

- Made in the U.S.A.
- Designed for professional use.
- Plastic dipped handles.

<b>No. D213-9NE</b>	Klein's most popular (9")	Wt: 1.25 lb.
<b>No. D2000-9NE</b>	Klein hardened jaws (9")	Wt: 1.25 lb.
<b>No. D2000-9NETH</b>	Klein with 5/8" thread cleaners	Wt: 1.25 lb.



420G



430G

## ADJUSTABLE PLIERS

- The original Channellock® plier.
- Made in the exact same standards that earned it a quality reputation.

<b>No. 420G</b>	9 1/2" with coated handles	Wt: 1.0 lb.
<b>No. 430G</b>	10" with coated handles	Wt: 1.0 lb.



BSK20



BSK25



BSK30



BSK50



1570-3

## LINEMEN'S SKINNING KNIVES

- Plastic handle.
- A ring for hanging on a tool belt or tool board.

<b>No. BSK20</b>	Curved point, 9 1/4" OAL	
	No ring	Wt: 0.5 lb.
<b>No. BSK25</b>	Curved point, 9 1/4" OAL	Wt: 0.5 lb.
<b>No. BSK30</b>	Curved point, 10" OAL	Wt: 0.5 lb.
<b>No. BSK50</b>	Curved point, for shotgun stick, 10" OAL	Wt: 0.5 lb.
<b>No. 1570-3</b>	Curved point, 10" OAL	Wt: 0.4 lb.



1550-4



44005



44218



44219

## KLEIN FOLDING LINEMEN'S KNIFE

- 2.5" hardened locking blades.

<b>No. 1550-4</b>	Wood grain plastic with ring	Wt: 1.0 lb.
<b>No. 44005</b>	Impact-resistant handle with rubber insert	Wt: 0.5 lb.
<b>No. 44218</b>	Skinning knife with replaceable blade	Wt: 0.5 lb.
<b>No. 44219</b>	Replacement blades (3 pack)	Wt: 0.1 lb.

# HAND TOOLS



## HAMMERS

- Made in the USA.

<b>No. B6232</b>	Vaughn line hammer	Wt: 2.0 lb.
<b>No. B832</b>	Klein claw hammer	Wt: 2.5 lb.
<b>No. B809</b>	Klein double face hammer	Wt: 2.5 lb.
<b>No. B816</b>	Klein linemen's hammer	Wt: 2.5 lb.
<b>No. 11417N</b>	Plumb waffle hammer	Wt: 2.5 lb.



## KLEIN SCREWDRIVERS

- Features a square shank, keystone tip, cushion grip.


<b>No. 600-4</b>	8 11/32" OAL, 1/4" tip width and 4" shank	Wt: 0.4 lb.
<b>No. 600-6</b>	10 15/16" OAL, 5/16" tip width and 6" shank	Wt: 0.5 lb.
<b>No. 600-8</b>	13 7/16" OAL, 3/8" tip width and 8" shank	Wt: 0.6 lb.
<b>No. 600-12</b>	17 7/16" OAL, 1/2" tip width and 12" shank	Wt: 1.0 lb.
<b>No. 602-7DD</b>	7" round shank demo driver	Wt: 0.5 lb.



## STAPLE STICKS

- Makes driving staples safer and more efficient.
- Simply load 12 staples ahead of time and hammer them through when needed.
- There is no fumbling, and the risk of a glove puncture is minimized.

<b>No. BSS2000</b>	Staple stick for 3/4" staples	Wt: 0.5 lb.
<b>No. BSS2001</b>	Staple stick for 1" staples	Wt: 0.5 lb.



## FOLDING RULES

- Features either an inside read or an outside read.

<b>No. 900-6</b>	Klein 6' inside read wood	Wt: 0.3 lb.
<b>No. 15</b>	Lufkin 6' dual read wood	Wt: 0.3 lb.
<b>No. 15FG</b>	Rigid 6' inside read fiberglass	Wt: 0.3 lb.

# EQUIPMENT INSPECTION

Bashlin's Climbing Equipment is to be inspected before each use. If in the course of your inspection any of your tools are found to be defective, they must be removed from service immediately. Follow your company procedures for replacement. If there are any questions, please contact us. Properly maintaining your equipment is an investment in your well-being.



## HOW TO INSPECT YOUR EQUIPMENT

Here are the components of your equipment that need to be carefully inspected. Remove any product from service that has any of the following conditions.

### TOOL BELTS

(ESTIMATED SERVICE LIFE 5-8 YEARS)


- (A) Hardware-electrical burns, cracks, deformation, loose attachment points.
- (B) Sewing-loose, cut, broken or frayed stitches.
- (C) Leather or Nylon material-Abrasion, fraying, cracking, cuts or chemical deterioration.
- (D) Rivets-loose or bent rivets.
- (E) Tool loops-holsters-bug bags-elongated loops, loose attachments, cut straps, worn bag bottoms.
- (F) Belt tongue-broken stitches, elongated holes, worn or abraded material.



### FALL RESTRAINTS/POLE STRAPS/ SECONDARY LANYARDS

(ESTIMATED SERVICE LIFE 1 - 4 YEARS)

- (1) Hardware-electrical burns, cracks, bends, deformation, loose attachment, improper latch movement and gate spring tension, sticking adjuster cams or carabiner gates, loose set screws.
- (2) Nylon, leather or rope-abrasion that exposes red wear indicator, cuts, fraying, broken stitches, chemical damage.



### CLIMBERS

(ESTIMATED SERVICE LIFE IS WHEN 2ND SET OF GAFFS HAVE WORN OUT)

- (A) Straps and pads-cuts, extreme abrasion, elongated holes, loose attachment points, chemical damage.
- (B) Shank-electrical burns, cracks, deformation, worn stirrup (thinning), improper slide adjustment. Careful inspection is required to the "critical" portion of the climber shank, 4-8" above the gaff attachment point. Scratches and cuts in this section may cause stress risers, accelerate wear and allow the shank to fail prematurely.
- (C) Gaffs-loose attachment, electrical burns, and incorrect shape. See Bashlin Information booklet BLCL514 for gaff shaping information, or go to [www.bashlin.com](http://www.bashlin.com) and see the gaff shaping video.



Additional detailed information is available by request or online.

## NOTES:

**"SUPERIOR PRODUCTS  
REQUIRE VISION AND  
SKILLED HANDS."**

**—W.M. BASHLIN, 1926**






## FALL PROTECTION AND RESCUE EQUIPMENT FOR LINEWORKERS AND GENERAL INDUSTRY

**Bashlin Industries, Inc.** offers field proven products and innovative engineered solutions for all your fall protection needs. Our products meet the ASTM, ANSI and OSHA requirements, including Arc Flash resistant harnesses and lanyards. In fact, we were one of the first companies to participate in the testing leading to the current ASTM Arc Flash standards.

# FALL PROTECTION EQUIPMENT GENERAL INFORMATION

## BASIC COMPONENTS OF FALL PROTECTION EQUIPMENT:



### A. ANCHORAGE/ANCHORAGE CONNECTORS:

A secure point that will endure the force of arresting a worker's fall. In most situations OSHA requires a strength rating of 5,000 lb. or more for a single worker's anchorage.

### B. HARNESS:

A device made of webbing, buckles, and D-Rings designed to hold the worker securely, distribute arresting forces, and provide a point to attach a lanyard connecting the individual to an anchorage.

### C. LANYARD:

A web product connecting the worker to the anchorage. It must include a shock absorbing device for fall arrest applications.

### D. CONNECTING DEVICES:

Snaphooks, carabiners, and D-Rings that link the various components of the personal fall protection equipment.

## FALL PROTECTION EQUIPMENT CRITERIA

Bashlin expands on these basic ideas for the specific desires of our customers. The big question is, what do you need? Here are some things to consider:

### ANCHORAGE/ANCHORAGE CONNECTORS:

- Does it have the required strength?
- Can it be easily accessed? Will the lanyards and fall lines remain clear of tangles and damaging edges?
- Are the connections and combinations of the hardware compatible to reduce the possibility of accidental disengagement or damage in an arrested fall?
- Are the connections close and as directly above the user as possible, and high enough to keep the worker from striking a lower level during an arrested fall?

### LANYARDS

- Are the lanyards as short as possible (6' maximum)?
- Does the free-fall distance comply with OSHA requirements?
- Do the connections to the anchorage and harness comply with industry standards?
- Is a shock absorber required or necessary?

### HARNESSES

- What are the OSHA requirements for the work situation?
- Does the work require positioning capabilities or only fall arrest?
- Can or will the fall protection equipment be used to aid in the rescue of a worker?

## INSPECT BEFORE EACH USE.

# PROPER USE AND CARE OF HARNESES



- Read, understand, and follow all instructional material included with or attached to these products.
- Do not use these products without proper training.
- Check that all buckle hardware and closures are aligned properly, are free from damage, and are functioning properly.
- Harness should be properly sized to the individual user. See page 37 for sizing chart.
- Adjust harness to obtain a “snug” fit by adjusting friction adjusters and buckles on shoulder and leg straps. When adjusted correctly the back attachment should be located between the shoulder blades of the user.
- Utilize elastic bands and plastic keepers to control excess webbing after adjustments are made.
- Avoid exposing safety harness to excessive heat, chemicals, and prolonged exposure to sunlight that can degrade the materials.

## CARING FOR YOUR HARNESS

Proper care for your harness is quick and easy by simply following these guidelines.

### CLEANING

“Hand Washing” is recommended using a mild laundry detergent. Rinse completely and hang to dry. Product can also be machine washed in a mesh bag on the gentle cycle. **DO NOT** machine dry.

### STORAGE

Store Harness in a ventilated area protected from moisture, heat, chemicals, and UV Light. Bashlin’s 10HB harness bag is a great storage option.



10HB



## INSPECTION

- Inspect before use.
- All tagging and labeling must be present and legible.
- Hardware should be free from electrical contact marks, cracks, deformities, corrosion, and must function properly.
- Webbing shall not have cuts, burns, broken stitching, excessive abrasion or chemical degradation.
- “Shock” load indicators are intact and have not been deployed.

**If any of the above issues are detected, remove product from service immediately.**



NYLON HARNESS EXPOSED TO ARC FLASH



UNDAMAGED UNDERSIDE OF SAME WEBBING



**BASHLIN HARNESSSES** are available in the X or H design. The X (683) models are sized. The H (662) are one size fits most.

**BASHLIN HARNESSSES AND LANYARDS ARE ASTM ARC FLASH COMPLIANT AND THIRD PARTY TESTED.**



683X



662



**BASHLIN'S NON-CONDUCTIVE BUCKLES, ADJUSTORS AND SNAPHOOKS ARE RATED AT 9KV.**

## X-STYLE & H-STYLE

BACK  
ATTACHMENT  
OPTIONS



ALUMINUM D-RING (D2)



DIELECTRIC D-RING (D1)



STANDARD D-RING (D)



NYLON WEB LOOP (A)

2' NYLON LOOP  
EXTENSION (B)2' SMALL D-RING  
EXTENSION (C)6' NYLON WEB LOOP  
WITH SMALL D-RING (C6)

### OPTIONS AVAILABLE (NOT PICTURED):

**LW06B:** 6' with B-LAN shock absorber  
**LWA6B:** 6' adjustable with B-LAN shock absorber  
**L2805-4HL:** 4' or 6' (6HL) polyester core/tubular web shock absorber



# ARC FLASH HARNESS OPTIONS

## X-STYLE

## H-STYLE

### HOW TO CORRECTLY CHOOSE BODY HARNESS OPTIONS:

- Choose a base harness style (ex.: 683X)
- Choose a back attachment(s) (ex.: 683XA)
- Choose other harness options (ex.: 683XAP)
- Choose a size (ex.: 683XAP-L)



SHOULDER D-RINGS (S)



DIELECTRIC BUCKLES (DEQ)



SHOULDER PADS (N)



NYLON WEB LOOPS ON SHOULDERS (T)



SHOULDER/BACK PAD COMBO (X)



QUICK RELEASE BUCKLES (Q) (PREFIX)



REFLECTIVE MATERIAL ON WEBBING (G)



656 SERIES POSITIONING BELT (D-SIZE REQUIRED) (P)



LEATHER BUCKLE PAD (F)



NEOPRENE BUCKLE PADS (G)



COATED HARDWARE (E)



RESCUE LOOPS ON CHEST (R)



ReSTEP SUSPENSION TRAUMA DEVICE (R2)


### SIZING CHART - BASED ON HEIGHT AND CHEST SIZE

#### X-STYLE 683 AND H-STYLE 662V

SIZE		HEIGHT	CHEST
S	Small	5' 4" - 5' 7"	36 in.
M	Medium	5' 8" - 5' 11"	40 in.
L	Large	6' 0" - 6' 3"	44 in.
X	X-Large	6' 3" - 6' 6"	48 in.
2XL	XX-Large	6' 6" +	52 in.
3XL	XXX-Large	6' 6" +	56 in.

#### H STYLE HARNESSES-662R AND 662A

SIZE		HEIGHT	CHEST
0	One Size Fits Most	5' 4" - 6' 3"	48 in.
X	X-Large	6' 3" - 6' 6"	54 in.
2X	XX-Large	6' 6" - 6' 10"	60 in.



# AERIAL LIFT AND GENERAL USE ARC FLASH HARNESSSES

## 683 "X" STYLE SERIES



The 683 "X" is Bashlin's premier body harness. Originally designed for the utility industry, this harness sets the standard for comfort, flexibility and ease of use. The hardware is low on the waist, and a loop is in the front for rescue or work positioning. Available with pass through friction buckles or quick release buckles. [Size required, see page 37.](#)

**BASHLIN'S HARNESSSES MEET ASTM F887 ARC-FLASH REQUIREMENTS AND ARE 3RD PARTY CERTIFIED**



683XC

## "X" HARNESS WITH 24" EXTENSION BACK ATTACHMENT

- X-Style full body harness.
- Pass through buckles.

<b>No. 683XB</b>	24" extension with nylon loop	Wt. 3.5 lb.
<b>No. 683XC</b>	24" extension with D-Ring	Wt. 3.5 lb.



683XD

## "X" HARNESS WITH D-RING BACK ATTACHMENT

- X-Style full body harness.
- 3" D-Ring.

<b>No. 683XD</b>	Pass through buckles	Wt. 4.0 lb.
<b>No. 683GD</b>	Grommet leg straps	Wt. 4.5 lb.



Shown with  
additional  
options  
BQ683XA

## "X" HARNESS B683X BLACK OUT SERIES

- X-Style full body harness.
- Black webbing with orange stitching.

<b>No. B683XA</b>	With nylon loop	Wt. 4.5 lb.
<b>No. B683XD</b>	With D-Ring	Wt. 4.5 lb.



683XA

## "X" HARNESS WITH NYLON LOOP BACK ATTACHMENT

- X-Style full body harness.
- 3" nylon loop for lanyard attachment.

<b>No. 683XA</b>	Pass through buckles	Wt. 4.0 lb.
<b>No. 683GA</b>	Grommet leg straps with pass through buckles	Wt. 4.5 lb.



683ID

## "X" HARNESS WITH BELT ATTACHMENT

- X-Style full body harness.
- Allows user to attach work belt to harness.

<b>No. 683IA</b>	With nylon loop	Wt. 4.5 lb.
<b>No. 683ID</b>	With D-Ring	Wt. 4.5 lb.

# AERIAL LIFT AND GENERAL USE ARC FLASH HARNESSES

## 662 "H" STYLE SERIES



The 662 Series is a fully adjustable, one size fits most full body harness, in the "H" style. This harness also has a dorsal seat strap and 10,000 lb. test web.

Size required, see page 37.



662RD

### "H" HARNESS WITH D-RING BACK ATTACHMENT

- H-Style full body harness.
- Pass through buckles.

<b>No. 662AD</b>	Moveable chest strap	Wt. 4.0 lb.
<b>No. 662RD</b>	Fixed chest strap	Wt. 4.0 lb.
<b>No. 662GD</b>	Moveable chest strap and grommet legs	Wt. 4.5 lb.



662RA

### "H" HARNESS WITH NYLON LOOP BACK ATTACHMENT

- H-Style full body harness.
- 1" nylon web loop.

<b>No. 662AA</b>	Moveable chest strap	Wt. 4.5 lb.
<b>No. 662RA</b>	Fixed chest strap	Wt. 4.0 lb.
<b>No. 662GA</b>	Moveable chest strap and grommet legs	Wt. 4.5 lb.



662AC

### "H" HARNESS WITH 24" EXTENSION BACK ATTACHMENT

- Available with or without 2" D-Ring.
- Use only with lanyards that are 4' or less.

<b>No. 662AB</b>	With loop end	Wt. 4.5 lb.
<b>No. 662AC</b>	With D-Ring	Wt. 4.5 lb.
<b>No. 662RB</b>	Fixed chest strap with nylon loop	Wt. 4.0 lb.
<b>No. 662RC</b>	Fixed chest strap with D-Ring	Wt. 4.0 lb.



662ID

### 662 "H" HARNESS WITH BELT ATTACHMENT

- H-Style full body harness.
- Allows user to attach work belt to harness.
- Nylon "A" loop or D-Ring back attachment available.

<b>No. 662ID</b>	Pass through buckles with D-Ring	Wt. 4.5 lb.
<b>No. 662IA</b>	Pass through buckles with nylon loop	Wt. 4.5 lb.



## DID YOU KNOW?

QUICK RELEASE BUCKLES ARE AVAILABLE  
ON ALL BASHLIN HARNESSES (Q).



# AERIAL LIFT AND GENERAL USE ARC FLASH HARNESSES



662VA

## "H" HARNESS 662VA

- H-Style full body harness with a nylon "A" loop or D-Ring back attachment.
- Hook-N-Loop chest closure with pass through friction buckles.
- Sized as an X-Style harness (S-2X). See page 37.

<b>No. 662VA</b>	Pass through buckles with nylon loop	Wt. 4.0 lb.
<b>No. 662VD</b>	Pass through buckles with D-Ring	Wt. 4.0 lb.

Shown with  
additional  
options  
BQ6662A

## "H" HARNESS B662A BLACK OUT SERIES

- 662 H-Style harness in black webbing and orange stitching.
- Moveable chest strap with pass through buckles.
- Size required, see page 37.

<b>No. B662AA</b>	With nylon loop	Wt. 4.5 lb.
<b>No. B662AD</b>	With D-Ring	Wt. 4.5 lb.

# DIELECTRIC HARNESSES



Bashlin's X-Style and H-Style harnesses are available with dielectric buckles and snap hooks constructed with nylon molded over heat treated alloy steel to produce a minimum rating of 9kV. Lanyards are also available. [Size required, see page 37.](#)



DEQ683XA

## "X" DIELECTRIC HARNESS

- Quick release buckles.
- Available with nylon "A" loop or dielectric D-Ring.
- Size required, see page 37.

<b>No. DEQ683XA</b>	Nylon web loop	Wt. 3.5 lb.
<b>No. DEQ683XD1</b>	Dielectric D-Ring	Wt. 4.5 lb.



DEQ662HA

## "H" DIELECTRIC HARNESS

- Quick release buckles.
- Available with nylon "A" loop or dielectric D-Ring.
- Size required, see page 37.

<b>No. DEQ662HA</b>	Nylon web loop	Wt. 4.0 lb.
<b>No. DEQ662HD1</b>	Dielectric D-Ring	Wt. 4.5 lb.



# CLIMBING, SUBSTATION, AND TOWER HARNESSSES



Shown with additional  
options Q6622ACGR2X.

## Q662ZA SERIES: ZEUS "H" STYLE ARC FLASH FULL BODY HARNESS

- At just 7.5 lbs. this full body H-Style harness has an integral stacked 4 D-Ring belt with aluminum D-Rings, quick release buckles, and Dri-Lex moisture wicking pad.
- Rescue loops on chest.
- Sizes as follows: Small (S) D18-21; Medium (M) D22-25; Large (L) D26-28; X-Large (X) D29-32.

**No. Q662ZA** Quick release buckles  
with nylon loop **Wt. 7.5 lb.**

### CALL US TO PLACE AN ORDER WITH ANY OF THE ADDITIONAL OPTIONS AVAILABLE:

- (A) Nylon loop dorsal attachment
- (C) 2' Extension
- (D2) Aluminum D-Ring
- (G) Neoprene buckle pads
- (R2) RESTEP Suspension Trauma Straps
- (X) Mesh shoulder/back pad



10HB

## HARNESS BAGS

- Store and protect your body harness from most mechanical, chemical and UV damage in this high visibility orange canvas bag.

**No. 10HB** Harness bag **Wt. 1.0 lb.**



683XAP  
Shown with  
"X" Pad.



## 683 "X" STYLE CLIMBING HARNESS

- Available with 656CM tool belt.
- Belt easily removed from harness.
- Front attachment point for work positioning on ladders or rescue.
- Size both harness and tool belt "D" size.

<b>No. 683XDP</b>	With 3" D-Ring	Wt. 8.0 lb.
<b>No. 683XAP</b>	With nylon loop	Wt. 8.0 lb.
<b>No. 683XBP</b>	With 24" loop extension	Wt. 8.0 lb.
<b>No. 683XCP</b>	With 24" D-Ring extension	Wt. 8.0 lb.



QFE683EZTWR

## FE683EZTWR TOWER HARNESS

- 683 X-Style harness
- Extra support and comfort EZ-Rider belt.
- Available with "A" loop or D-Ring.
- Size both harness and tool belt "D" size.

**No. FE683EZTWR** Pass through buckle **Wt. 11.0 lb.**



## DID YOU KNOW?

QUICK RELEASE BUCKLES ARE AVAILABLE  
ON ALL BASHLIN HARNESSSES (Q).

# HARNESSES FOR CONFINED SPACE, RESCUE



BEDQ683XD1



683XDT



## BEDQ683XD1 "X" STYLE HARNESS

- Dielectric D-Ring with 18" nylon loop choked into D-Ring.
- Four "A" loops with reflexite (two on shoulders and two on hips).
- Leather buckle pads.
- Size required, see page 37.

No. **BEDQ683XD1** X-Style harness

Wt. 4.5 lb.

## CONFINED SPACE HARNESS

- Bashlin standard 683X and 662 H-Style harnesses for confined space entry are available with specialty options such as shoulder loops, hip loops, and high visibility material on webbing.
- Available in X-Style or H-Style.
- Pass through buckles standard.

No. **683XDT**

D-Ring, nylon shoulder loops

Wt. 4.0 lb.

No. **662ACS**

24" D-extension and  
shoulder D-Rings

Wt. 5.0 lb.



BED662VDEF



## BED662VDEF "H" STYLE HARNESS

- Dielectric D-Ring with 18" nylon loop choked into D-Ring.
- Four "A" loops with reflexite (two on shoulders and two on hips).
- Coated hardware.
- Leather buckle pads.
- Hook-N-Loop and loop chest closure.
- Size required, see page 37.

No. **BED662VDEF** H-Style harness

Wt. 4.5 lb.



## 683X HARNESS OPTIONS (EX.):

683X STYLE HARNESS (683XC6EQT) WITH 6" EXTENSION, SMALL D-RING, COATED HARDWARE, REFLEXITE, AND NYLON SHOULDER LOOPS.

## DID YOU KNOW?

QUICK RELEASE BUCKLES ARE AVAILABLE ON ALL BASHLIN HARNESSES (Q).

# LANYARDS FOR AERIAL LIFT/ FALL PROTECTION



**BASHLIN'S LANYARDS MEET ASTM F887 ARC-FLASH REQUIREMENTS AND ARE 3RD PARTY CERTIFIED**



## 2000 SERIES B-LAN SHOCK ABSORBING LANYARDS

The B-LAN shock absorber pack reduces shock forces to the user by drawing the nylon web through a compressed steel tube (as a result of a fall event).

**The maximum and standard length of the 2000 series lanyard is 6'. Shorter lengths are available on request.**



### No. 2004NWB-6HL

Shock absorbing lanyard. 1" nylon web with B-LAN and two SL6650A rope snaphooks.

Wt. 2.5 lb.



### No. 2005NWB-6HL

Shock absorbing lanyard – 1" nylon web with B-LAN, a SL6650A rope snaphook and a loop end.

Wt. 2.0 lb.



### No. 2005NWB-6DE

1" nylon web with B-LAN, a non-conductive dielectric snaphook, and a loop end.

Wt. 1.75 lb.



### No. 2015NWB-6HL

Shock absorbing lanyard – 1" nylon web with B-LAN, a SL6650A rope snaphook and a 3005A aluminum carabiner.

Wt. 2.0 lb.



### No. 2017NWB-6HL

Shock absorbing lanyard – 1" nylon web with B-LAN, a SL6650A rope snaphook and a 3005 steel carabiner.

Wt. 2.0 lb.



### No. 2002NWB-6HL

Shock absorbing lanyard – 1" nylon web with B-LAN, a SL6650A rope snaphook and a 5395A large ladder snaphook.

Wt. 3.0 lb.

# LANYARDS FOR AERIAL LIFT/ FALL PROTECTION



BASHLIN'S LANYARDS MEET ASTM F887 ARC-FLASH REQUIREMENTS AND ARE 3RD PARTY CERTIFIED



## 2800 SERIES-POLYESTER SHOCK ABSORBING CORE

The 2800 series lanyards are constructed using tubular nylon web with a woven polyester core that absorbs forces as it expands in a fall event.

The maximum and standard length of the 2800 series lanyard is 6'. Shorter lengths are available on request.



### No. 2804-6HL

Shock absorbing lanyard – tubular nylon web with polyester shock absorbing core and two SL6650A snaphooks.

Wt. 2.5 lb.



### No. 2805-6HL

Shock absorbing lanyard – tubular nylon web with polyester shock absorbing core, a SL6650A snaphook and a loop end.

Wt. 2.0 lb.



### No. 2805-6DE

Shock absorbing lanyard – tubular nylon web with polyester shock absorbing core, a non-conductive dielectric snaphook and a loop end.

Wt. 2.0 lb.



### No. 2815-6HL

Shock absorbing lanyard – tubular nylon web with polyester shock absorbing core, a SL6650A snaphook and a 3005A carabiner.

Wt. 2.0 lb.



### No. 2817-6HL

Shock absorbing lanyard – tubular nylon web with polyester shock absorbing core, a SL6650A snaphook and a 3005 carabiner.

Wt. 2.0 lb.



### No. 2802-6HL

Shock absorbing lanyard – tubular nylon web with polyester shock absorbing core, a SL6650A snaphook and a 5395A large snaphook.

Wt. 3.5 lb.



# LANYARDS FOR AERIAL LIFT/ FALL PROTECTION



 BASHLIN'S LANYARDS MEET ASTM F887 ARC-FLASH REQUIREMENTS AND ARE 3RD PARTY CERTIFIED

## 2300 SERIES-POLYESTER SHOCK ABSORBING CORE WITH "STRETCH"

The 2300 series lanyards are constructed using tubular nylon web with a woven polyester core that absorbs forces as it expands in a fall event. Elastic cord has been added to allow the lanyard to "stretch" and contract minimizing length while using. Standard length is 6'.



### No. 2317-6HL

Shock absorbing "stretch" lanyard – 2" tubular nylon web with polyester shock absorbing core, a SL6650A snaphook and a 3005 carabiner.

Wt. 2.0 lb.



### No. 2306-6HL

Shock absorbing "stretch" lanyard – 2" tubular nylon web with polyester shock absorbing core and two SL6650A snaphooks.

Wt. 2.5 lb.



### No. 2302-6HL

Shock absorbing "stretch" lanyard – 2" tubular nylon web with polyester shock absorbing core, a SL6650A snaphook and a 5395A large ladder hook. Wt. 3.5 lb.



### No. 2305-6HL

Shock absorbing "stretch" lanyard – 2" tubular nylon web with polyester shock absorbing core, a SL6650A snap hook, and a loop end.

Wt. 2.0 lb.



### No. 2315-6HL

Shock absorbing "stretch" lanyard – 2" tubular nylon web with polyester shock absorbing core, a SL6650A snaphook and a 3005A carabiner.

Wt. 1.5 lb.



**WARNING:** Limiting the lanyard length to 6' will not ensure a free fall of 6' or less. The lanyard length, plus anchor point and work location together will determine the free fall distance.



## DID YOU KNOW?

### BASHLIN LANYARDS ARE AVAILABLE WITH THE FOLLOWING OPTIONS AND FEATURES:

- Forged steel snaphooks (SL6650A), steel carabiner (3005), aluminum carabiners (3005A), or large ladder snap (5395A).
- 1" nylon web, and 1" tubular web.
- Manufactured to ANSI, ASTM, and OSHA requirements.

# 2-LEG LANYARDS FOR CLIMBING TOWERS



## B-LAN SERIES

The B-LAN shock absorber pack reduces fall arrest forces in a fall event by drawing the nylon web through a compressed steel tube.

## B-LAN STYLE - "Y" CLIMBING LANYARD



### No. 2028NWB-6HL

Twin leg climbing lanyard with steel rope snap, two large steel ladder hooks, and B-LAN shock absorber.

Wt. 5.0 lb.



### No. 2028-6AL

Twin leg climbing lanyard with aluminum rope snap, two large aluminum ladder snaphooks, and B-LAN shock absorber.

Wt. 5.0 lb.



### No. 2027-6HL

Twin leg climbing lanyard with nylon loop, two large steel ladder snaphooks, and B-LAN shock absorber.

Wt. 5.0 lb.



**CAUTION:** Lanyards may be connected to D-Rings on harnesses (D) with web/rope loops, and properly dimensioned carabiners or snaphooks. Nylon back attachments, (C) require web/rope loops or properly dimensioned carabiners. Snaphooks are not to be used with (C) attachment points. See page 49.



HITCHING A LANYARD TO A HARNESS.



Large ladder snap hooks have a 2.5" opening.

# 2-LEG LANYARDS FOR CLIMBING TOWERS



## POLYESTER SHOCK ABSORBING CORE STYLE - "Y" CLIMBING LANYARD

The 2300/2800 series lanyards are constructed using tubular nylon web with a woven polyester core that absorbs forces as it expands in a fall event. Standard length is 6'

AVAILABLE IN SHORTER LENGTHS UPON REQUEST.



### No. 2327-6HL

Twin leg tubular nylon "stretch" climbing lanyard with nylon loop, two large steel ladder snaphooks, and shock absorbing core.

Wt. 5.0 lb.



### No. 2827-6AL

Twin leg tubular nylon climbing lanyard with nylon loop, two large aluminum ladder snaphooks, and shock absorbing core.

Wt. 4.5 lb.



### No. 2328-6HL

Twin leg tubular nylon "stretch" climbing lanyard with steel snap hook, two large steel ladder snaphooks, and shock absorbing core.

Wt. 5.5 lb.



### No. 2328-6AL

Twin leg tubular nylon "stretch" climbing lanyard with aluminum snap hook, two large aluminum ladder snaphooks, and shock absorbing core.

Wt. 5.0 lb.



### No. 2827-6HL

Twin leg tubular nylon climbing lanyard with nylon loop, two large steel ladder snaphooks, and shock absorbing core.

Wt. 5.0 lb.



### No. 2828-6HL

Twin leg tubular nylon "stretch" climbing lanyard with steel snap hook, two large steel ladder snaphooks, and shock absorbing core.

Wt. 5.0 lb.

# POSITIONING LANYARDS



## 4000 SERIES – FIXED LENGTH POSITIONING LANYARDS

This series is designed for and mostly used in positioning applications. In certain situations they can be used for fall arrest, if they are used with a shock absorbing device and if all other applicable requirements are met.

The maximum and standard length of the 4000 series lanyard is 6'. Shorter lengths are available on request.



### No. 4005NW-6HL

1" nylon web with SL6650A rope snaphook and one loop end.

Wt. 2.0 lb.



### No. 4002NW-6HL

1" nylon web with SL6650A rope snaphook and 5395A large ladder snaphook on the ends.

Wt. 3.5 lb.



### No. 4017NW-6HL

1" nylon web with SL6650A rope snaphook and 3005 steel carabiner on the ends.

Wt. 2.5 lb.



### No. 4004NW-6HL

1" nylon web with SL6650A rope snaphooks on the ends.

Wt. 2.5 lb.





# PROPER USE AND CARE OF LANYARDS



- Read, understand, and follow all instructional material included with or attached to these products. (A)
- Inspect before use.
- Make sure connector on end of lanyard is compatible with harness and anchor point and working properly. (B)
- Do not attach a snap hook directly into a nylon back attachment. (C) Use a locking carabiner or a lanyard that has loop at one end that can be "hitched" to the nylon loop. (D)

- Do not connect two lanyards together to make a lanyard as this will increase your free fall potential. (E)
- Do not use "knots" to shorten a lanyard as this will decrease the strength of the device by 30% or more. (F)
- Do not connect snap hook back into itself (boiler hitch). (G)
- Utilize parking tabs to store free end of lanyard to reduce tripping and entanglement hazards when walking. (H)
- Avoid dragging or allowing lanyards to lay on ground exposing it to chemical or mechanical damage.

## INSPECTION

- Inspect before use.
- All tagging and labeling must be present and legible.
- Hardware should be free from electrical contact marks, cracks, deformities, corrosion, and must function properly.
- Webbing shall not have cuts, burns, broken stitching, excessive abrasion, or chemical degradation.
- "Shock" Load indicators are intact and have not been deployed.

If any of the above issues are detected, remove product from service immediately.

## CARING FOR YOUR LANYARD

Proper care for your Lanyard is quick and easy by simply following these guidelines.

### CLEANING

"Hand Washing" is recommended using a mild laundry detergent. Rinse completely and hang to dry. Product can also be machine washed in a mesh bag on the gentle cycle. **DO NOT** machine dry.

### STORAGE

Store Lanyard in a ventilated area protected from moisture, heat, chemicals, and UV light.

# ANCHORAGES/CONNECTORS



703



703R-2D

## BOOM STRAPS



- 10,000 lb. test nylon web.
- Nylon pads.
- Corrosion resistant.
- Standard length is 55"

<b>No. 703</b>	Boom strap with friction buckle	Wt. 2.0 lb.
<b>No. 703R</b>	Boom strap with ratchet	Wt. 3.5 lb.
<b>No. 703R-2D</b>	2 D-Ring boom strap for overcenter lifts	Wt. 4.5 lb.



**WARNING:** Bashlin boom straps, even those with 2 D-Rings are for one worker only. Each worker must have his/her own individual anchorage.



B3732

## ANCHORAGE CONNECTORS



- Can be permanently secured to a structure.
- Tested to 5,000 lbs.

<b>No. B3732</b>	4.25" x 2.9" with 2.8" opening	Wt. 1.0 lb.
------------------	--------------------------------	-------------



2011P



2011P1



2012P

## NYLON ANCHOR STRAPS



- Rated at 5,000 lb.
- Standard 3' or 4' lengths.
- Longer lengths are available on request.

<b>No. 2011P-36</b>	36" anchor strap with hardware	Wt. 1.75 lb.
<b>No. 2011P-48</b>	48" anchor strap with hardware	Wt. 1.75 lb.
<b>No. 2011P1-36</b>	36" anchor strap	Wt. 1.0 lb.
<b>No. 2011P1-48</b>	48" anchor strap	Wt. 1.0 lb.
<b>No. 2012P-36</b>	36" anchor strap	Wt. 0.7 lb.
<b>No. 2012P-48</b>	48" anchor strap	Wt. 0.7 lb.



**CAUTION:** Nylon anchor straps require padding for protection over sharp edges.

# HARDWARE/DESCENT DEVICES

## CARABINERS



These are convenient connectors for many applications. Only triple locking carabiners are to be used for fall protection. Bashlin's carabiners are rated at a minimum of 5000 lb. (\*OAL is overall length).



### TRIPLE LOCK DESIGN FOR FALL PROTECTION SYSTEMS



<b>No. 3006</b>	Steel 5" OAL with 1" gate opening	Wt. 1.0 lb.
<b>No. 3008A</b>	Aluminum 47/8" OAL with 7/8" gate opening	Wt. 0.3 lb.



### TWIST LOCK AND SCREW LOCK CARABINERS

- For rescue and material handling.

<b>No. 3006K</b>	Steel twist lock 5" OAL with 1" opening	Wt. 0.9 lb.
<b>No. 3004</b>	Steel screw lock 5" OAL with 1 1/4" opening	Wt. 1.1 lb.



SL6650A

## ROPE SNAPHOOKS



- Forged steel rated at a minimum of 5000 lb. and meeting the OSHA and ANSI standards.

<b>No. SL6650A</b>	5 9/16" OAL 3/4" gate opening	Wt. 0.5 lb.
--------------------	-------------------------------	-------------



5395A

## LARGE SNAPHOOKS



- Forged steel rated at a minimum of 5000 lb. and meeting the OSHA and ANSI standards.

<b>No. 5395A</b>	9" OAL 2 1/2" gate opening	Wt. 2.0 lb.
------------------	----------------------------	-------------



3200



DSD30

## ROPE DESCENT DEVICES

<b>No. 3200</b>	Russ Anderson rescue "8" with ears for 7/16" and 1/2" rope OAL 6"	Wt. 2.0 lb.
<b>No. DSD30</b>	Skylotec double stop descender 11mm 7/16" static lines	Wt. 2.06 lb.



**CAUTION:** This equipment is to be used by trained personnel only.

- Inspect before use.
- Always place the anchor point as high as possible to reduce free fall distance and the chance that the worker could impact a lower level should a fall event occur.
- **DO NOT** use nylon web anchor slings around structures or objects with sharp edges unless softeners are used to protect the sling from sharp edges.

- Inspect before use.
- All tagging and labeling must be present and legible.
- Hardware should be free from electrical contact marks, cracks, deformities, corrosion, and must function properly.
- Webbing shall not have cuts, burns, broken stitching, excessive abrasion, or chemical degradation.

**Store Nylon Anchor in a ventilated area protected from moisture, heat, chemicals, and UV light.**

## NOTES:



# AERIAL SELF RESCUE EQUIPMENT

## PARA-PAK

The Para-Pak is a self contained kit for emergency evacuation from an elevated work area.

The basic device consists of a 3/8" Aramid fiber line packed into a low profile cartridge. 75' of line stores in an 10" x 10" pouch less than 2" thick.

It's much smaller and weighs less than similar products that use 1/2" synthetic line. The thin profile and lightweight make this a very versatile and user friendly system.

## PARA-PAK RESCUE KIT

- Combination of 683 harness, Para-Pak and lanyard.
- Requires the 683X Series harness to connect to the Para-Pak and a 6" back attachment point extension.
- The FR-Nomex Para-Pak includes a pre-rigged nylon ladder and clips to connect to the harness pad.
- Requires a lanyard that has a ring or loop for connecting to the rescue line.
- Can't be retrofitted on existing fall arrest harnesses or lanyards.

<b>No. 683XC6</b>	X-Style harness with 6" loop and D-Ring	Wt. 4.5 lb.
<b>No. SR700XPL</b>	Para-Pak with shoulder pad mounting system for harness	Wt. 2.5 lb.
<b>No. SR2804-5.5HL</b>	Lanyard with rescue ring	Wt. 2.5 lb.



**AS SHOWN:**  
683XC6 AND  
SR700XPL

## EMERGENCY SELF EVACUATION FROM AN AERIAL LIFT

### SR PACK

- Evacuation or rescue from an elevated work area.
- Lightweight and easy to carry.
- Weather resistant pouch and has a mechanical descent device that will stop if the control is released.
- A harness with a front attachment is required.

<b>No. SRPACK-100AL</b>	Rescue Pack (100 ft.)	Wt. 3.3 lb.
-------------------------	-----------------------	-------------



SRPACK-100AL

# REST SERIES: RELIEF FOR SUSPENSION TRAUMA



ReST

## ReST - SUSPENSION TRAUMA DEVICE

- Designed to mitigate the debilitating and potentially fatal effects of suspension trauma.
- Ladder secures to the back attachment of the worker's harness for easy access and deployment.
- Easily deploys by pulling on yellow rung.

No. ReST      Suspension trauma ladder      Wt. 0.7 lb.



ReST-SR

## ReST SR - SUSPENSION TRAUMA RELIEF LADDER

- Self-deploying relief system.
- Ladder can provide the worker a means for either self-rescue, or at the very least a place to relieve the pressure on the leg as a result of hanging in the harness for an extended period of time after a fall event.
- Adjustable for use on 4' - 6' lanyards.
- Can be used on most lanyards.

No. ReST-SR      Self-rescue ladder      Wt. 1.2 lb.



ReSTeP



## ReSTeP SUSPENSION TRAUMA DEVICE

- Simple and easy device designed to help minimize and alleviate the damaging and potentially fatal effects of suspension trauma when a worker is exposed to a fall event and left suspended in a upright position.
- Easily attaches to most harnesses.

No. ReSTeP      Suspension trauma device      Wt. 0.5 lb.

# RESCUE EQUIPMENT



700FP



700FWI



700FWI (OPEN)

## RESCUING INJURED WORKERS FROM AERIAL LIFT DEVICES

- Designed for use in aerial lift devices.
- 700FP attaches semi-permanently to the boom with a ratcheting boom strap.
- 700FWI is stored in a canister mounted directly on the truck body.
- Units feature corrosion resistant blocks with nylon sheaves and 75' of twisted rope. Other rope lengths are available on request.
- A carabiner is provided for attachment to the victim.
- Proper training is required to use these items.

<b>No. 700FP</b>	Boom mount rescue pack	Wt. 8.0 lb.
<b>No. 700FWI</b>	Truck mount rescue pack	Wt. 14.0 lb.



## WRISTLETS

- Quick and easy way to move an injured worker.
- Nylon straps with 3" loops and soft felt padding.

<b>No. 696NW</b>	Wristlets	Wt. 0.5 lb.
------------------	-----------	-------------



FE700SRKSC

## AERIAL LIFT-SELF RESCUE

- Designed for personal evacuation from a stranded aerial lift.
- 50' of 7/16" polydyne rope with an anchor eye spliced on one end, two carabiners, an DSD30 double stop descender and a carrying bag.
- Available as a boom-mount device.
- Proper training is required to use this item.
- Longer line is available.

<b>No. FE700SRKSC</b>	Aerial self rescue kit	Wt. 5.0 lb.
<b>No. FE700BMSRSC</b>	Boom mount rescue kit	Wt. 5.5 lb.



Check out our website for a video on how to use the 700FP.

# RETRACTABLE LIFELINES

## RETRACTABLE LIFELINES



- “B110” series features an aluminum housing while the “B120” series has a more durable steel housing. Both of these units utilize wire or kevlar rope.
- “B130” series uses flat strap polyester webbing.
- The snap hook features a shock load indicator to help determine when the device should be removed from service.

<b>No. B110G-25</b>	Aluminum housing lifeline 25'	Wt. 20.0 lb.
<b>No. B110G-50</b>	Aluminum housing lifeline 50'	Wt. 26.0 lb.
<b>No. B110G-100</b>	Aluminum housing lifeline 100'	Wt. 45.0 lb.
<b>No. B120G-30</b>	Steel housing lifeline 30'	Wt. 20.3 lb.
<b>No. B120G-50</b>	Steel housing lifeline 50'	Wt. 26.0 lb.
<b>No. B120G-65</b>	Steel housing lifeline 65'	Wt. 27.0 lb.
<b>No. B130W-20</b>	Steel housing 20'	Wt. 13.0 lb.
<b>No. B130W-30</b>	Steel housing 30'	Wt. 13.0 lb.



B110G-25



B120G-30



B130W-20

## NOTES:





#### BAGS, BUCKETS, AND TOOL CARRIERS

**Bashlin Industries, Inc.** has a wide assortment of tool carriers for utility work. We fabricate them from canvas, nylon, and durable synthetics. They are designed for all sorts of job applications to make your work easier.

# GEAR BAGS, BACK PACKS AND TOOL BAGS

## BACK PACK SERIES

- Made from coated polyester and canvas materials.
- These durable and versatile gear bags offer the user plenty of room for storage of tools and gear.
- Available in yellow, black, orange, and camo.
- Features high visibility orange canvas liner.



11BPD-B



11BPD-C



11BPD-Y

## 11BPD BACK PACK DUFFLE

- Interior lined with high visibility orange material making what you're looking for easy to find.
- Draw string closure with buckles to secure top cover.
- Padded back with adjustable shoulder straps and rubberized handle.
- Front Pocket: 16" x 16" x 4".

<b>No. 11BPD-B</b>	Black, 26"H x 50"C (around)	Wt. 6.0 lb.
<b>No. 11BPD-O</b>	Orange, 26"H x 50"C (around)	Wt. 6.0 lb.
<b>No. 11BPD-Y</b>	Yellow, 26"H x 50"C (around)	Wt. 6.0 lb.
<b>No. 11BPD-C</b>	Camo, 26"H x 50"C (around)	Wt. 6.0 lb.



11BP-O

## 11BP TOP LOAD BACK PACK

- 3 exterior pockets (front: 12"x12"x4"/2 side: 16"x6"x3).
- Buckles secure top cover.
- Coated polyester with a hard plastic bottom.
- Padded back with adjustable shoulder straps and rubberized handle.

<b>No. 11BP-B</b>	Black, 16"W x 9" x 19"H	Wt. 6.0 lb.
<b>No. 11BP-O</b>	Orange, 16"W x 9" x 19"H	Wt. 6.0 lb.
<b>No. 11BP-Y</b>	Yellow, 16"W x 9" x 19"H	Wt. 6.0 lb.
<b>No. 11BP-C</b>	Camo, 16"W x 9" x 19"H	Wt. 6.0 lb.



11BPM-Y



11BPM-C

## 11BPM BACK PACK MINI

- Compact bag for PPE or any small load.
- Rubber handle.
- Padded adjustable straps.

<b>No. 11BPM-B</b>	Black, 18"H x 38"C (around)	Wt. 1.5 lb.
<b>No. 11BPM-O</b>	Orange, 18"H x 38"C (around)	Wt. 1.5 lb.
<b>No. 11BPM-Y</b>	Yellow, 18"H x 38"C (around)	Wt. 1.5 lb.
<b>No. 11BPM-C</b>	Camo, 18"H x 38"C (around)	Wt. 1.5 lb.



10S-14



10S-14TC

## 10S SERIES

- This durable bag is made of heavy canvas.
- Constructed with a steel frame, polyester web handles, and either a reinforced coated polyester bottom or hard plastic bottom.

<b>No. 10S-14</b>	Small bag with hard plastic bottom 14" x 10" x 7"	Wt. 4.0 lb.
<b>No. 10S-14T-C</b>	Small bag 14" x 15" x 7 with hard plastic bottom - camo	Wt. 4.25 lb.
<b>No. 10S-18</b>	Mid-size bag with coated polyester bottom 18" x 12" x 9"	Wt. 5.0 lb.
<b>No. 10S-22</b>	Medium bag with coated polyester bottom 22" x 12" x 7"	Wt. 5.75 lb.
<b>No. 10S-24</b>	Large bag hard plastic bottom 24" x 12" x 7"	Wt. 5.75 lb.

# GEAR BAGS, BACK PACKS AND TOOL BAGS



11DCS

## 11DC SERIES

- Made of durable coated polyester.
- Nylon web handles.
- Hard plastic bottom and flap to cover the opening.
- The "S" model features a polyester web shoulder strap.

**No. 11DC** 24" x 19" x 11" Wt. 8.0 lb.

**No. 11DCS** With shoulder strap Wt. 8.0 lb.



12S



12SC

## 12S SERIES

- This bag is made of canvas or coated polyester.
- It has a steel frame with polyester web handles and hard plastic bottom.
- Features inside and outside pockets.
- The "S" model features a polyester web shoulder strap.
- Also available in black, yellow, orange and camo.

**No. 12S** 22" x 13" x 11" Wt. 8.0 lb.

**No. 12SS** 22" x 13" x 11" with shoulder strap Wt. 9.0 lb.

**No. 12SC** 22" x 13" x 11" coated polyester Wt. 8.0 lb.

**No. 12SCS** 22" x 13" x 11" coated polyester with shoulder strap Wt. 9.0 lb.



DL11DC-RB-C



DL11DC-RB-O

## DL11DC-RB SERIES: LARGE WHEEL "DRAG" BAG

- Has a hard plastic bottom and nylon web handles.
- Large 6" all terrain wheels.
- Features a flap to cover the opening when exposed to weather.
- Extendable handle.
- Available in black, yellow, orange and camo.

**No. DL11DC-RB** 24" x 19" x 11" bag on large wheels Wt. 10.0 lb.



DL11DC-R

## DL11DC-R: ROLLER BAG

- Has a hard plastic bottom and nylon web handles.
- Features a flap to cover the opening when exposed to weather.
- Durable nylon wheels with an extendable handle.
- Available in black, yellow, orange and camo.

**No. DL11DC-R** 24" x 19" x 11" bag on wheels Wt. 7.0 lb.



## CUSTOM LOGOS AND MARKING

Contact customer service for more information about having your custom logo on our canvas and poly-coated products. There is no additional cost for making the product, simply a one time screen set up fee!



# GLOVE/SLEEVE BAGS



24M



24MC



24L



24LC



24LB



24LBC



24XL2P

## LINEMEN'S GLOVE BAGS

- Best way to ensure proper protection of rubber gloves.
- Constructed from durable canvas or coated polyester.
- Features a snap button closure and an attachment hook.
- Includes drain holes in the bottom.
- Available with a bellows opening which is wider at the top for easier storage.
- Two pocket bags are good for keeping high voltage and low voltage gloves separate.
- Add "C" to part number for coated bags.

<b>No. 24M</b>	Standard opening (10 1/2" gloves)	Wt. 0.5 lb.
<b>No. 24</b>	Standard opening (14" gloves)	Wt. 0.7 lb.
<b>No. 24B</b>	Bellows opening (14" gloves)	Wt. 0.7 lb.
<b>No. 24L</b>	Standard opening (16" gloves)	Wt. 0.7 lb.
<b>No. 24LB</b>	Bellows opening (16" gloves)	Wt. 0.8 lb.
<b>No. 24XL</b>	Standard opening (18" gloves)	Wt. 0.8 lb.
<b>No. 24XLB</b>	Bellows opening (18" gloves)	Wt. 0.8 lb.
<b>No. 24L2P</b>	2 pocket glove bag (16" gloves)	Wt. 1.10 lb.
<b>No. 24XL2P</b>	2 pocket glove bag (18" gloves)	Wt. 1.10 lb.



24SLV



## LINEMEN'S SLEEVE BAGS

- Constructed from durable canvas or coated polyester.
- Hanging loop and attachment hook standard.
- Optional Snap button or Hook-N-Loop closure.

<b>No. 24SL</b>	Sleeve bag	Wt. 1.0 lb.
<b>No. 24SLV</b>	Hook-N-Loop closure sleeve bag	Wt. 1.0 lb.



24SLGP-19



24SLGPC-19

## GLOVE/SLEEVE BAGS

- Standard size sleeve bag combined with the glove bag.
- Available in coated polyester.
- Add "C" to part number for coated bags
- Add a pocket for safety glasses by including "GP" in the part number.

<b>No. 24SLGP-15</b>	For 14" rubber gloves	Wt. 1.5 lb.
<b>No. 24SLGP-17</b>	For 16" rubber gloves	Wt. 1.6 lb.
<b>No. 24SLGP-19</b>	For 18" rubber gloves	Wt. 1.70 lb.



# BLANKET BAGS, ROLLS, CANISTERS



24RBR-38



24RBR-38

## BLANKET ROLLS

- Easy way to store and carry rubber blankets.
- Constructed from durable canvas with four blanket capacity.
- Features nylon snap closures and a nylon web carrying handle.

**No. 24RBR-38** For 36" blankets  
**No. 24RBR-47** For 46" blankets

Wt. 1.5 lb.  
 Wt. 2.0 lb.



24RBC-38

## BLANKET BAGS

- Blanket bags are made of heavy duty coated polyester. They have reinforced seams for added durability.

**No. 24RBC-38** For 36" blankets Wt. 1.10 lb.  
**No. 24RBC-47** For 46" blankets Wt. 1.5 lb.



BC136-2 BC136-3 BC136-4

## BLANKET CANISTERS

- Blanket canisters make storage easy while providing mechanical and contamination protection.
- Made of high impact polyethylene.

<b>No. BC136-2</b>	5" x 37" (capacity: 2)	Wt. 2.5 lb.
<b>No. BC136-3</b>	6" x 37" (capacity: 3)	Wt. 2.75 lb.
<b>No. BC136-4</b>	7" x 37" (capacity: 4)	Wt. 3.25 lb.
<b>No. BC136-6</b>	9" x 37" (capacity: 6)	Wt. 4.75 lb.



208-42 212-48

## LINE HOSE BAGS

- Cotton bags that make handling and storage of line hose easier.
- Reinforced tops, and leather bottoms.

<b>No. 208-30</b>	8" x 30"	Wt. 2.0 lb.
<b>No. 208-42</b>	8" x 42"	Wt. 2.5 lb.
<b>No. 208-48</b>	8" x 48"	Wt. 3.0 lb.
<b>No. 208-60</b>	8" x 60"	Wt. 3.5 lb.
<b>No. 210-30</b>	10" x 30"	Wt. 3.0 lb.
<b>No. 210-42</b>	10" x 42"	Wt. 3.5 lb.
<b>No. 210-48</b>	10" x 48"	Wt. 4.0 lb.
<b>No. 210-60</b>	10" x 60"	Wt. 4.5 lb.
<b>No. 212-30</b>	12" x 30"	Wt. 3.5 lb.
<b>No. 212-42</b>	12" x 42"	Wt. 4.0 lb.
<b>No. 212-48</b>	12" x 48"	Wt. 4.5 lb.
<b>No. 212-60</b>	12" x 60"	Wt. 5.0 lb.

# HOT STICK, GROUND SET BAGS



24HCS



270B

## HOT STICK BAGS

- Protective bags that are made from coated polyester material and feature a snap button closure.
- Order according to the length of the stick and size as indicated with the stick description.

<b>No. 24HSC-30</b>	30" hot stick bag	Wt. 1.5 lb.
<b>No. 24HSC-45</b>	45" hot stick bag	Wt. 2.0 lb.
<b>No. 24HSC-60</b>	60" hot stick bag	Wt. 1.5 lb.
<b>No. 24HSC-65</b>	65" hot stick bag	Wt. 2.0 lb.
<b>No. 24HSC-75</b>	75" hot stick bag	Wt. 1.5 lb.
<b>No. 24HSC-80</b>	80" hot stick bag	Wt. 2.0 lb.
<b>No. 24HSC-100</b>	100" hot stick bag	Wt. 1.5 lb.
<b>No. 24HSC-125</b>	125" hot stick bag	Wt. 2.0 lb.
<b>No. 24HSC-130</b>	130" hot stick bag	Wt. 1.5 lb.
<b>No. 270B</b>	Rescue stick bag for #270	Wt. 2.0 lb.
<b>No. 1967B</b>	Bag for 1967RCP	Wt. 1.5 lb.

## GROUND SET BAGS

- Bashlin's ground set bags are an easy way to store and carry grounding equipment.



217

## COATED POLYESTER BAG

- Extra heavy bag is made of coated polyester material.
- It has web handles and a Hook-N-Loop closure.

**No. 217** 28 1/2" x 25 1/2" Wt. 1.5 lb.



10S-14

## 10S SERIES

- This durable bag is made of heavy canvas.
- Includes a steel frame, polyester web handles and hard plastic bottom.

<b>No. 10S-14</b>	Small bag with hard plastic bottom 14" x 10 x 7"	Wt. 4.0 lb.
<b>No. 10S-24</b>	Large bag hard plastic bottom 24" x 12" x 7"	Wt. 5.75 lb.

# TOOL BUCKETS, HARNESS AND TOOL BAGS



## TOOL BUCKETS

- Bashlin tool buckets are made of the highest quality materials for long life.
- Available in canvas or coated polyester and feature leather or plastic bottoms.
- Inside pockets are standard on the 23 series buckets.
- 'LS' series buckets have no snaps.
- Add "C" for coated bags.

### LEATHER BOTTOM:

<b>No. 18</b>	8" x 12"	Wt. 1.5 lb.
<b>No. 18LS</b>	8" x 12" - no snap	Wt. 1.25 lb.
<b>No. 23</b>	12" x 16"	Wt. 3.75 lb.
<b>No. 23LS</b>	12" x 16" - no snap	Wt. 3.5 lb.

### PLASTIC BOTTOM:

<b>No. 18P</b>	8" x 12"	Wt. 1.5 lb.
<b>No. 18P-O</b>	8" x 12", orange	Wt. 1.5 lb.
<b>No. 18LSP</b>	8" x 12" - no snap	Wt. 1.25 lb.
<b>No. 23P</b>	12" x 16"	Wt. 3.75 lb.
<b>No. 23LSP</b>	12" x 16" - no snap	Wt. 3.5 lb.



## 700 SERIES: AERIAL BAGS

- Non-conductive frame to keep the bag open.
- Reinforced bottom.
- Ten inside pockets for tools.
- 14" x 7" x 10.

<b>No. 706</b>	Tool bag with PVC hooks	Wt. 3.0 lb.
<b>No. 706S</b>	Tool bag with rope and snap	Wt. 3.0 lb.



## 717 SPLICER'S TOOL BAG

- Non-conductive frame to keep the bag open.
- Tool pockets inside and 14 outside pockets.
- Reinforced bottom.

<b>No. 717</b>	14 1/2" x 7" x 9 1/2"	Wt. 3.0 lb.
----------------	-----------------------	-------------

# AERIAL TOOL BAGS AND TOOL CARRIERS



706-20

## 706-20

- 20" deep and has 10 inside pockets.
- Includes 712 hooks.

No. 706-20

14" x 7" x 20"

Wt. 3.25 lb.



721AM



722AM

## TOOL BUCKET/BAG FOR "SHOOT ON" CONNECTORS

- Bashlin manufactures both a tool bucket and a bag for the "shoot on" connectors.
- Ample storage for the cartridges, the tool, as well as the connectors and wedges.
- Includes 712 hooks for hanging in bucket.
- The bucket includes a snap on the rope.
- Available in canvas or coated polyester.

No. 721AM

Tool bag (8" x 12", polyester) Wt. 2.0 lb.

No. 722AM

Tool bucket (8" x 12", polyester) Wt. 2.5 lb.

No. 723AM

Tool bucket (8" x 12", canvas) Wt. 2.0 lb.



726

## COMPRESSION TOOL AND CUTTER BAG

- Three pocket coated polyester bag.
- Two pockets are for compression tools, one is for bolt cutters.
- Two PVC hooks are included.

No. 726

12" x 20"

Wt. 3.5 lb.



10HB

## HARNESS BAGS

- Store and protect your body harness from most mechanical, chemical and UV damage in this high visibility orange canvas bag.

No. 10HB

Harness bag

Wt. 1.0 lb.



# TOOL BOARDS

## TOOL CARRIERS

Bashlin's tool boards are made of ABS. This light, durable material does not fray or flake and has superior cold weather characteristics. These boards are built and arranged with the worker in mind. They save precious space in the bucket and keep the tools in a handy position.



708



708L

## HAMMER/HAND TOOLS/ BOLTS AND NUTS

- This is our original tool board. It remains a popular design with many utilities.
- 18" x 20".
- Features a 4 pocket tool holster, knife sheath, tool loops, and leather or canvas nut and bolt bag.

**No. 708**

With 25B bag

Wt. 6.25 lb.

**No. 708L**

With 26L bag

Wt. 7.0 lb.



708S

## HAND TOOLS/PRUNING SAW/ BOLT CUTTER

- A pruning saw, more tools and cutter can be easily carried on this board.
- The #26R canvas bag has extra reinforcement for extended wear.
- 18" x 20".

**No. 708S**

With 26R bag

Wt. 8.5 lb.



708-2

## COMPRESSION TOOL/BITS/ HAND TOOLS

- This board holds a variety of most often used tools.
- Holds speed wrenches, hammers, compression tools, and a light.
- 18" x 20".

**No. 708-2**

With 726 and 25B bags

Wt. 7.0 lb.



708ID

## HAND TOOLS/DRIVERS

- This aerial lift tool board complements our popular 708 Tool Board Series.
- Designed by Niagara Mohawk, it is perfect for aerial lifts that use an impact driver and need a convenient socket holder.
- Carries 6, 1/2" drive sockets on the tool board. It firmly holds the sockets with extra long socket stems that can accommodate all deep well sockets.

**No. 708ID**

With 25B Bag

Wt. 14.0 lb.

# TOOL BOARD/TOOL TRAY



708G

## 708G

- Includes spaces for drill bits, drivers, and the Lowell wrench.
- 18" x 20".

**No. 708G** Tool board with 26L bag Wt. 12.0 lb.



708B

## BLANK TOOL BOARD

- Blank ABS tool boards allowing you to customize a tool board to suit your needs.
- 18" x 20".

**No. 708B** Blank tool board Wt. 4.0 lb.



724

## TOOL APRON

- Made from yellow heavyweight coated nylon.
- It has socket pockets, 2 pockets for auger bits, a hammer loop, and 2 large pockets for bolts, nuts and connectors.
- 2 PVC hooks are included.
- 23 7/8" x 21 1/4"

**No. 724** Tool apron Wt. 5.0 lb.



727L

## TOOL TRAY

- This tool tray features an adjustable mount and smooth molded construction.
- 6" x 14" x 7 1/2".

**No. 727L** Tool tray Wt. 8.0 lb.



712

712-2

712-3




712P-2

712P-3

## HOOKS

- PVC and polymer hooks for hanging bags and tool aprons.

<b>No. 712</b>	PVC-3" buckets PVC	Wt. 0.21 lb.
<b>No. 712-2</b>	PVC-standard buckets	Wt. 0.21 lb.
<b>No. 712-3</b>	PVC-3" lip buckets	Wt. 0.21 lb.
<b>No. 712P</b>	Polymer-standard buckets	Wt. 0.31 lb.
<b>No. 712P-3</b>	Polymer-3" lip buckets	Wt. 0.31 lb.




700BK

## BUCKET KNUCKLE

- Tool holding and organization bracket designed to suspend and separate tools inside an aerial device.
- Durable UHMW plastic.
- Measures 19 3/4" x 3" x 2 1/2".
- Hang from two standard bucket hooks (not included).
- Made in USA.

**No. 700BK** Bucket knuckle Wt. 1.5 lb.

# SAFETY HOOK/BUCKET COVER



BSH20

BSH50

## SAFETY HOOK

- Rugged hook with a break strength in excess of 250 lb.
- It will safely replace many hooks formed from #8 copper hanging on line trucks everywhere.

<b>No. BSH20</b>	Double hook	Wt. 0.6 lb.
<b>No. BSH50</b>	Single bar with 3 double hooks	Wt. 1.5 lb.



731CS

## CHAIN SAW HOLDER

- This tool holder hangs on the outside of the bucket and will hold cutters, compression tools and/or a chain saw.
- Made of ABS plastic.
- Durable in all temperature ranges.

<b>No. 731CS</b>	Tool holder	Wt. 5.0 lb.
------------------	-------------	-------------



745

745

## REINFORCED BUCKET COVER

- Rugged coated polyester with or without foam insert.
- Designed for 24" x 24" bucket.
- Rope and snap hook to help secure to bucket.

<b>No. 744</b>	Soft bucket cover	Wt. 4.4 lb.
<b>No. 745</b>	Reinforced bucket cover	Wt. 6.7 lb.



## NOTES:

**W.M. BASHLIN COMPANY BEGINS OPERATION  
IN 1926, PROMISING "COMFORT, QUALITY  
AND SAFETY" FOR THE PROFESSIONAL LINEMAN.**





## LINE VEHICLE EQUIPMENT AND CONSTRUCTION TOOLS

**Bashlin Industries, Inc.** makes and sells quality tools and equipment for the professional lineworker. This includes slings, winchlines, payout reels, hot sticks, and more.

We specialize in the hard-to-find equipment unique to this market.

# SLINGS/POLE SLINGS

## NYLON SLINGS

- Rugged 950 Series orange nylon slings are made for the utility industry and to current ANSI standards.
- Standard length is 3 feet.
- Other lengths available upon request.



950-100




950-300

## ENDLESS SLINGS

LOAD RATING LBS.				
	WIDTH	VERTICAL	CHOKER	BASKET
No. 950-100	1"	3200	2560	6400
No. 950-100D	1" DT	6200	4960	12400
No. 950-175	1 3/4"	4000	3200	8000
No. 950-175D	1 3/4" DT	8800	7040	17600
No. 950-200	2"	5600	4480	11200
No. 950-200D	2" DT	12200	9760	24400
No. 950-300	3"	8000	6400	16000
No. 950-300D	3" DT	15200	12160	30400



951-100



951-175



951-200

## DOUBLE EYE STANDARD

LOAD RATING LBS.				
	WIDTH	VERTICAL	CHOKER	BASKET
No. 951-100	1"	3200	2560	6400
No. 951-175	1 3/4"	5400	4320	10800
No. 951-200	2"	6400	5120	12800
No. 951-300-4	3"	7800	6240	15600



**WARNING:** Always inspect slings before use. Heavily abraded, burned, or cut slings should be removed from service.



Contact customer service for abrasion resistance wear pads or custom slings.

## DOUBLE EYE SINGLE PLY

LOAD RATING LBS.				
	WIDTH	VERTICAL	CHOKER	BASKET
No. 952-100	1"	1600	1280	3200
No. 952-175	1 3/4"	2800	2240	5600
No. 952-200	2"	3200	2560	6400
No. 952-300-4	3"	4200	3360	8400



953-200

## RETURN EYE

LOAD RATING LBS.				
	WIDTH	VERTICAL	CHOKER	BASKET
No. 953-200	2"	5600	4480	11200
No. 953-350	3 1/2"	7600	6080	15200

## GRIP SLINGS

- Rubber belting sewn onto the fabric to reduce slippage.
- 1 3/4" nylon slings are available with or without 5000 lb. test O-Ring.
- The 4" soft eyes have ballistic nylon wear sleeves.



2011SE-52G

LOAD RATING LBS.			
	VERTICAL	CHOKER	BASKET
<b>No. 2011SE-52G</b> 52" with steel ring	2500	2500	5000
<b>No. 2011SE-72G</b> 72" with steel ring	2500	2500	5000
<b>No. 2012SE-52G</b> 52" with 2 soft eyes	3300	2640	6600
<b>No. 2012SE-72G</b> 72" with 2 soft eyes	3300	2640	6600

## POLE SLINGS

- Pole slings are available with (2011) or without (2012) hardware. The 2011 is designed for easy use with a shotgun stick.



2011-36

LOAD RATING LBS.					
	WIDTH	VERTICAL	CHOKER	BASKET	WT.
No. 2011-36	1 3/4"	1000	1000	2000	1.75 lb.
No. 2011-48	1 3/4"	1000	1000	2000	1.75 lb.
No. 2012-36	1 3/4"	3300	2640	6600	0.7 lb.
No. 2012-48	1 3/4"	3300	2640	6600	0.7 lb.

# ROPE SLINGS/AUGER SLINGS

## YALE ADJUSTABLE ROPE SLINGS

- Whoopee slings make awkward lifts much easier. They are available in Polyale Plus™ or Yalex™ rope.



		LOAD RATING LBS.		
		VERTICAL	CHOKER	BASKET
<b>No. 960P</b>	1/2" Polyale Plus™			
	Adj. 28" - 48"	1496	1197	2992
<b>No. 960Y</b>	5/8" Yalex™			
	Adj. 32" - 60"	3203	2562	6406
<b>No. 960YL</b>	5/8" Yalex™			
	Adj. 32" - 96"	3203	2562	6406



- The double leg adjustable rope sling features a center lifter point, with a protective cover and adjustment on both legs.
- Available in either 1/2" Polyale Plus™ or 5/8" Yalex™ rope, and is ideal for hanging transformers.

		LOAD RATING LBS.		
		VERTICAL	CHOKER	BASKET
<b>No. 962P</b>	1/2" Polyale Plus™			
	Adj. 30" - 50"	1496	1197	2992
<b>No. 962Y</b>	5/8" Yalex™			
	Adj. 30" - 50"	3203	2562	6406



- For pad mount transformers, we have the four legged sling. Each leg adjusts individually for quick rigging.


		LEG LENGTH	LOAD RATING
<b>No. 965P</b>	1/2" Polyale Plus™	4' - 5'	4550 lb.
<b>No. 965Y</b>	5/8" Yalex™	5' - 7'	12820 lb.
<b>No. 965YL</b>	5/8" Yalex™	6' - 8'	12820 lb.
<b>No. 965V</b>	5/8" Vectrus™	5' - 7'	32010 lb.

## FIXED LENGTH ROPE SLINGS

- Rope slings are made from 5/8" Yalex™ rope. The standard length is 3' for the endless, 4' for double eye.



		LOAD RATING LBS.		
		VERTICAL	CHOKER	BASKET
<b>No. 4950-58Y</b>	5/8" endless sling	6188	4950	12376
<b>No. 4951-58Y</b>	5/8" double eye std.	3640	2912	7280



## AUGER WIND UPS

- Strong, light-weight featuring reinforced eyes.
- Standard length is 10' (other lengths are available).

<b>No. 770W</b>	1" x 10' nylon web	Wt. 1.15 lb.
<b>No. 770R</b>	5/8" x 10' Yalex™	Wt. 2.0 lb.
<b>No. 770RDE</b>	1" x 10' double esterlon	Wt. 4.0 lb.



962NWTs

## 962NWTs: ADJUSTABLE NYLON TRANSFORMER SLING

- 1,000 lb. load rating.
- Features large rings to fit over the lifting hooks.

<b>No. 962NWTs</b>	Adjustable nylon transformer sling	Wt. 1.6 lb.
--------------------	------------------------------------	-------------



# HANDLINES AND SLACK BLOCKS



940

## HANDLINES

- 1/2" Polyale Plus™ braided rope is the standard rope for all 940 series handlines. It is easily spliced and resists rotation under load.
- Standard 940 includes 500 lb. SWL 35H drop forged alloy steel handline hook, SL6650A steel double locking snaphook, 75' of rope, and premium block.
- 940R comes with a 35H hook, 75' of rope, and steel snaphook.

<b>No. 940</b>	Complete handline assembly 500 lb. SWL*	Wt. 8.75 lb.
<b>No. 940R</b>	Rope only with 35H hook and snaphook - 500lb. SWL*	Wt. 6.75 lb.
<b>No. 940HD10</b>	Aluminum hook and aluminum snaphook - 1000 lb. SWL*	Wt. 9.0 lb.


\*SWL - Safe Working Load.



940HD10



945



945T

## SLACK BLOCK ASSEMBLY

- Slack blocks come with 30' of 3/8" Polyale Plus™ or polyester twist rope.
- "H" series features extended hooks.
- The maximum safe working load is 750 lb. SWL\*

<b>No. 945</b>	Polyale Plus™	Wt. 4.25 lb.
<b>No. 945H</b>	Polyale Plus™ with extended hooks	Wt. 4.25 lb.
<b>No. 945T</b>	Poly-Twist	Wt. 4.25 lb.
<b>No. 945HT</b>	Poly-Twist with extended hooks	Wt. 4.25 lb.



## PARTS FOR HANDLINES

<b>No. 33</b>	Handline carrier	Wt. 0.1 lb.
<b>No. 33L</b>	Locking handline carrier	Wt. 0.1 lb.
<b>No. 35H</b>	Handline hook - 500 lb. SWL*	Wt. 0.75 lb.
<b>No. 35GP</b>	Double hook - 100lb. SWL*	Wt. 0.6 lb.
<b>No. DNHLH5</b>	Aluminum hook -1000 lb. SWL*	Wt. 0.7 lb.
<b>No. 3550</b>	Handline block	Wt. 2.0 lb.

\*SWL - Safe Working Load.



For handlines longer than 75' contact customer service



# WINCH LINES/PULLING LINES



## WINCH LINES

Bashlin will fabricate replacement winch lines for your material handling and digger trucks. Our splicers are certified by Yale Cordage annually and can manufacture to your specifications. Call us for pricing and delivery.

**Ask about our winch line maintenance program.**



## DOUBLE ESTERLON WINCH LINES

- Yale Double Esterlon is low stretch, high strength rope with excellent dielectric properties.
- Maxijacket coating on the end provides abrasion resistance where you need it.
- Color coded coatings can make it easy to determine when it is time to replace your lines.
- 1/2" and 1" Double Esterlon available.

**No. 750DE12W08** 1/2" Double Esterlon winchline with 8' of Maxijacket coating. Average breaking strength 10,500 - 2,625 lb. working load (4/1) 8.1 lb. per 100'

**No. 750DE10W08** 1" Double Esterlon Winchline with 8' of Maxijacket coating. Average breaking strength 44,000 - 11,000 lb. working load (4/1) 35.2 lb. per 100'



Spools, shields, and shackles are available for your winch lines. Call for a quote.

## MAXIBRAID PLUS WINCH LINES

- Maxibraid Plus™ is a double braided rope constructed of an inner load bearing core of UHMPE that is very strong with very little stretch. UHMPE has the highest strength to weight ratio of any high modulus fiber.
- The core is coated with Maxijacket™ coating then a polyester jacket is overbraided for a long wearing extra strong line.

**No. 750MP12W0** 1/2" Maxibraid Plus™ winchline with Maxijacket™ coating. Average breaking strength 20,000 - 4,000 lb. working load (5/1) 7.3 lb. per 100'.

**No. 750MP78W0** 7/8" Maxibraid Plus™ winchline with Maxijacket™ coating. Average breaking strength 50,000 - 10,000 lb. working load (5/1) 23.2 lb. per 100'.

**We can repair your worn and damaged lines when possible.**



## PULLING LINES INCLUDING PILOT LINES AND SPIDER LINES

- We recommend Yalex™ for all your stringing applications. Yalex™ is a single braid 12 strand polyester rope coated with Maxijacket™ for abrasion resistance. It is easy to splice, and is the strongest Yale polyester product.
- Call for part number, pricing and delivery.



# PULLING GRIPS AND HOISTS



1685-20



1671-10

## KLEIN PARALLEL JAW GRIPS

- The Klein parallel jaw grips have longer jaws for less slippage and conductor damage.

	MIN. CABLE	MAX. CABLE	SAFELOAD	WT.
No. 1686-10	.20	.40	10,000 lb.	5.0 lb.
No. 1686-20	.20	.40	10,000 lb.	5.0 lb.
No. 1671-10	.37	.75	10,000 lb.	5.0 lb.
No. 1672-10	.37	.75	10,000 lb.	5.0 lb.
No. 1685-20	.157	.844	4,500 lb.	3.0 lb.
No. 1685-31	.625	1.25	6,600 lb.	5.0 lb.



LMG4500



LMG4501

## LITTLE MULE GRIPS

- These parallel jaw grips resist jamming and will release instantly. The design reduces cable damage.

### STANDARD GRIPS:

	MIN. CABLE	MAX. CABLE	SAFELOAD	JAWS	WT.
No. LMG1000	.04	.394	1,000 lb.	Serrated	0.5 lb.
No. LMG2000	.109	.594	2,000 lb.	Serrated	1.0 lb.
No. LMG4500	.18	.60	5,000 lb.	Serrated	3.75 lb.
No. LMG4600	.30	.80	10,000 lb.	Serrated	6.50 lb.
No. LMG4800	.70	1.25	12,000 lb.	Serrated	9.0 lb.

### HOT LINE GRIPS:

	MIN. CABLE	MAX. CABLE	SAFELOAD	JAWS	WT.
No. LMG4501	.18	.60	5,000 lb.	Serrated	4.0 lb.
No. LMG4601	.30	.80	10,000 lb.	Serrated	7.0 lb.
No. LMG4801	.70	1.25	12,000 lb.	Serrated	9.0 lb.



300A

## LITTLE MULE STRAP HOIST

- The 300 Series hoists are designed for line work. They are light, easy to handle, and rugged. All of the working parts are exposed for easy field repair.

	SINGLE LINE CAPACITY	SINGLE LINE LIFT LENGTH	DOUBLE LINE CAPACITY	DOUBLE LINE LENGTH	WT.
No. 300A	1,500 lb.	9'	3,000 lb.	4.5'	10.5 lb.
No. 300DA	1,500 lb.	9'	3,000 lb.	4.5'	11.0 lb.



PA2000

## CM TORNADO CHAIN HOIST

- Racheting chain hoist with swivel hooks.

	SINGLE LINE CAPACITY	SINGLE LINE LIFT LENGTH	WT.
No. PA2000	3,000 lb.	5	21.1 lb.



903LT

## 903LT: LIF-T

- Great for pad mount transformers.
- 5/8" grade 8 construction with handle.
- Orange corrosion resistant powder coating.
- Sold as a pair.
- 1,000 lb. capacity.

No. 903LT: LIF-T Lifting T

Wt. 0.5 lb.

# CROSS ARM IRON, PAY-OUT REELS AND GROUND ROD DRIVERS



900



900X

## PAY-OUT REELS

- Fully adjustable, all purpose device for use on trucks or as a portable pay-out reel.
- Works on many different coil sizes.
- Standard grease fitting provides full lubrication.
- Adjustable brake maintains line tension.
- 900-900X coil capacity.
- Diameter: 14" (minimum) - 32" (maximum)
- Width: 6" (minimum) - 11" (maximum)

	HEIGHT	WIDTH	DEPTH	WT.	SHIP WT.
<b>No. 900</b>	40"	37"	19"	145 lb.	175.0 lb.
<b>No. 900S</b>	35"	32"	19"	95 lb.	120.0 lb.
<b>No. 900X</b>	45"	37"	19"	165 lb.	180.0 lb.



901LF



901TI

## CROSS ARM IRON

- Here is an easier way to rig for lifting a transformer (901LF), or sagging a line (901TI). These versatile anchors can be placed in position with a hot stick even if pre-rigged. The load rating is 500 lb.

<b>No. 901LF</b>	Cross arm iron	Wt. 3.5 lb.
<b>No. 901TI</b>	Cross arm iron II	Wt. 3.5 lb.



902

## WIRE BASKET

- Lightweight, compact wire dispenser that will accommodate reels up to 26" x 4 1/4".
- Features a hanger for easy mounting on a truck and an eyelet for temporary pole attachment.

<b>No. 902</b>	Wire basket	Wt. 11.0 lb.
<b>No. 902-30</b>	30" wire basket	Wt. 12.0 lb.



930



930UT

## GROUND ROD DRIVER

- Designed to ease the chore of driving ground rods.
- Compact, safe, easy to handle and store.
- Enables a workman to drive an 8' rod while standing on the ground.
- The 930UT features hand guards.
- 1/2", 5/8" and 3/4" ground rods.

<b>No. 930</b>	Ground rod driver	Wt. 20.0 lb.
<b>No. 930UT</b>	Ground rod driver with hand guard	Wt. 24.0 lb.

# CUTTERS AND URD DISCONNECT TOOL

Porter ratchet cutters use the combination ratchet and chain for smooth, progressive cuts. The handles are insulated and factory tested. Parts are available for field repairs.



8690FH

## 8690FH

- A 29 1/4" cutter for shearing cuts on ACSR and common steel.

**No. 8690FH**      13/16" jaw opening      Wt. 12.25 lb.



8690CK

## 8690CK

- A rugged 28", extra-duty cutter for EHS guy strand. The jaws hold the wire for square, clean cuts.

**No. 8690CK**      7/16" jaw opening      Wt. 11.0 lb.



BC18F




BC24F

## CUTTERS WITH FIBERGLASS HANDLES

- Handles are tested to 100kv per foot.

**No. BC18F**      18" length, 3/8" capacity      Wt. 4.5 lb.

**No. BC24F**      24" length, 7/16" capacity      Wt. 4.5 lb.



RJL1967RCP

## URD DISCONNECT TOOL

- Original LeVesque URD disconnect featuring three jaw operation and a pusher rod for smooth disconnects. It is done with a minimum of strain and chafing on the semi-conductor. It tests at 100 kV per foot.
- The standard length is 5'. Other lengths are available on request.

**No. RJL1967RCP**      Tool      Wt. 10.5 lb.


**No. 1967B**      Carrying case      Wt. 1.25 lb.



# SWITCH STICKS AND SHOTGUN STICKS

## HASTINGS HOT STICKS

- Recognizable by their bright yellow color, they are the finest insulated tools available to the professional lineman.



567-6

## FIXED LENGTH UNIVERSAL HEAD SWITCH STICKS

- These fixed length sticks have a universal head for use with most hot stick accessories.
- Stick Hanger is included.

<b>No. 567-6</b>	6' length	Wt. 1.4 lb.
<b>No. 567-8</b>	8' length	Wt. 2.6 lb.
<b>No. 567-10</b>	10' length	Wt. 3.3 lb.
<b>No. 567-12</b>	12' length	Wt. 4.0 lb.



1901-6

UNIVERSAL  
OPTIONBOTTOM BREAK  
HOOK OPTION

## SHOTGUN STICKS

- Shotgun sticks with eternal operating rods, hanger hook, and end caps.

<b>No. 1901-6</b>	6' - 6" length	Wt. 4.5 lb.
<b>No. 1901-10</b>	10' - 6" length	Wt. 7.2 lb.

## TELESCOPING SWITCH STICKS

- Hastings Tel-O-Pole sticks feature the easy to hold sure lock triangle shape
- Fluorescent green tip section with foam core



HV208

## STANDARD DUTY TEL-O-POLE II

- The "No Twist" stick.

	EXTENDED LENGTH	RETRACTED LENGTH	WT.
<b>No. HV208</b>	8'	26"	3.0 lb.
<b>No. HV212</b>	12' - 7"	58"	3.7 lb.
<b>No. HV225</b>	25' - 6"	64"	8.1 lb.
<b>No. HV230</b>	30'	66"	10.0 lb.
<b>No. HV235</b>	35'	68"	12.1 lb.



SH216

## HEAVY DUTY TEL-O-POLE

	EXTENDED LENGTH	RETRACTED LENGTH	WT.
<b>No. SH216</b>	9' - 13' - 17'	58 1/8"	4.8 lb.
<b>No. SH200</b>	13' - 17.5' - 21.5'	60"	6.57 lb.
<b>No. SH230</b>	13'-17.5'-21.5'-26'-30'	63 3/8"	10.3 lb.



Hot Stick accessories available upon request. Sticks over 5' will be shipped via motor freight. Other length sticks available upon request.

# ELECTRICIAN'S/INSTALLERS HOLSTERS, AND BELTS

## HOLSTERS

Bashlin holsters put your tools where you want them, within easy reach. They are designed with the worker in mind and made with only the highest quality leathers and the finest craftsmanship.

**These holsters are not for use on linemen's tool belts.**



111YS



111YSX

### 111YS

- Sturdy holster with a harness leather back.

**No. 111YS** 9 1/4" x 10 1/2" Wt. 1.25 lb.

**No. 111YSX** 9 1/4" x 10 1/2" - black Wt. 1.25 lb.



111JBS



111JBSX

### 111JBS

- Built from select leathers and is made to last.

**No. 111JBS** 8 1/2" x 9" x 4" Wt. 1.25 lb.

**No. 111JBSX** 8 1/2" x 9" x 4" - black Wt. 1.25 lb.



111JLMS



111JLMSX

### 111JLMS

- If you are carrying a lot of tools, this may be the holster you need. It is our largest multipurpose holster.

**No. 111JLMS** 12" x 9" x 4 3/4" Wt. 2.0 lb.

**No. 111JLMSX** 12" x 9" x 4 3/4" - black Wt. 2.0 lb.



112HLS



112HLSX

### 112HLS

- Harness leather backed groundman's holster for pliers, rule, screwdriver, and Channellock®.

**No. 112HLS** 7 1/2" x 12"

Wt. 1.0 lb.

**No. 112HLSX** 7 1/2" x 12" - black

Wt. 1.0 lb.



112CIL



112CILX

### 112CIL

- Large cable installer with extra pockets.

**No. 112CIL** 8" x 12"

Wt. 1.0 lb.

**No. 112CILX** 8" x 12" - black

Wt. 1.0 lb.



625

630

628

## ELECTRICIAN'S BELTS

- Add "X" to part number for black.
- Specify a size.

**No. 625** 1 3/4" russet leather utility belt

Wt. 1.0 lb.

**No. 628** 1 3/4" electrician's belt will carry a hammer, tape, and a knife with the holster

Wt. 1.0 lb.

**No. 630** Heavy duty 2" belt with a double tongue buckle.

Wt. 1.25 lb.



## ELECTRICAL PERSONAL PROTECTIVE EQUIPMENT

**Bashlin Industries, Inc.** has been a major supplier of electrical personal protective equipment for many years. We offer rubber gloves, protectors, blankets, line hose and all of the accessories. We can also help you out with your special needs. Just give us a call.

# LINEMEN'S RUBBER GLOVES

High quality, natural rubber type I gloves have textured inside surface, "curved hand" comfort and flexibility.

## WHEN PURCHASING LINEMEN'S GLOVES, PLEASE CONSIDER:



ONE FINGER  
MITTEN

STANDARD

LOW VOLTAGE

## STYLE:

- Available in standard, bell cuff, one finger mittens and special order glove.



## GLOVE LENGTH:

- CLASS 00, 0:** 10 1/2", 14"
- CLASS 1, 2:** 14", 16", 18"
- CLASS 3:** 16", 18"
- CLASS 4:** 18"

## VOLTAGE RATING:

CLASS	LABEL	COLOR	MAXIMUM USAGE	AC TEST VOLTAGE
00		Beige	500v	2,500v
0		Red	1,000v	5,000v
1		White	7,500v	10,000v
2		Yellow	17,500v	20,000v
3		Green	26,500v	30,000v
4		Orange	36,000v	40,000v



## DID YOU KNOW?

OUR GLOVES ARE 100% TESTED FOR VISUAL FLAWS AND IMPERFECTIONS, AND ARE ELECTRICALLY TESTED PER ASTM STANDARDS.

IF REQUESTED, IN SERVICE DATING CAN BE MARKED ON THE GLOVES. CERTIFIED THIRD PARTY TESTING BY A NAIL CERTIFIED LAB IS AVAILABLE ON REQUEST.



## COLORS:

- Manufactured in solid colors or two contrasting colors for easier inspection. The lighter color is inside and the black is on the outside. Two color gloves are normally Class 1 and higher.



## SIZE:

- Sized according to the circumference of the hand below the base of the fingers, on a line parallel to the base of the finger crotches, passing through the thumb crotch. Add 1" to the measurement for the proper size.

## ORDER NUMBER/SPECIFICATIONS:

	MAX. USAGE	CLASS	AC TEST VOLTAGE	COLOR	SIZE
<b>No. 1100Y</b>	500v	00	2,500	Yellow	10 1/2"
<b>No. 110Y</b>	1,000v	0	5,000	Yellow	10 1/2"
<b>No. 140Y</b>	1,000v	0	5,000	Yellow	14"
<b>No. 14-10B</b>	7,500v	1	10,000	Black	14"
<b>No. 14-20B</b>	17,000v	2	20,000	Black	14"
<b>No. 16-20B</b>	17,000v	2	20,000	Black	16"
<b>No. 18-20B</b>	17,000v	2	20,000	Black	18"
<b>No. 14-20YB</b>	17,000v	2	20,000	Yellow/Black	14"
<b>No. 16-20YB</b>	17,000v	2	20,000	Yellow/Black	16"
<b>No. 18-20YB</b>	17,000v	2	20,000	Yellow/Black	18"
<b>No. 16-30YB</b>	26,500v	3	30,000	Yellow/Black	16"
<b>No. 18-30YB</b>	26,500v	3	30,000	Yellow/Black	18"
<b>No. 18-40B</b>	36,000v	4	40,000	Black	18"
<b>No. 18-40YB</b>	36,000v	4	40,000	Black	18"



# LEATHER PROTECTOR GLOVES AND LINERS



1050

1057



1200

910/999

## KUNZ LEATHER PROTECTOR GLOVES

- Bashlin offers the Kunz protectors for primary (high voltage) and secondary (low voltage) linemen's gloves.
- Made in the U.S.A. Bashlin offers the following protectors:
  - 1050 Series:** cream cowhide (primary)
  - 1057 Series:** bucktan cowhide (primary)
  - 1200 Series:** goatskin (primary)
  - 999 Series:** goatskin (secondary)
  - 910 Series:** goatskin (class 00)
- Made from 2.75 to 3.5 oz soft and pliable leather. The cowhide is popular and long wearing. The goatskin offers the best dexterity.
- Protectors for one finger mittens and bell cuff gloves are also available. Contact customer service for ordering information.
- Order by rubber glove size. Bashlin offers whole sizes only. Round half sizes up to the next whole size for proper fit. For 40KV gloves, add 1 full size for proper fit.

### FOR EXAMPLE:

Linemen's glove size 9 1/2 = protector size 10

Linemen's glove size 10 = protector size 10

## ORDER NUMBER/SPECIFICATIONS:

	USAGE/ VOLTAGE	O.A.L. LENGTH/STYLE	MATERIAL	WT.
<b>No. 910</b>	Low	8" with strap	Goatskin	0.4 lb.
<b>No. 999S</b>	Low	9" with strap	Goatskin	0.4 lb.
<b>No. 999</b>	Low	9"	Goatskin	0.4 lb.
<b>No. 1050-3</b>	High	12"	Cream Cowhide	0.6 lb.
<b>No. 1200-3</b>	High	12"	Goatskin	0.6 lb.
<b>No. 1057-3</b>	High	12"	Buck Tan Cowhide	0.6 lb.
<b>No. 1050-3BC</b>	High	12" Bell Cuff	Cream Cowhide	0.6 lb.
<b>No. 1200-3BC</b>	High	12" Bell Cuff	Goatskin	0.6 lb.
<b>No. 1057-3BC</b>	High	12" Bell Cuff	Buck Tan Cowhide	0.6 lb.
<b>No. 1050-5</b>	High	14"	Cream Cowhide	0.7 lb.
<b>No. 1200-5</b>	High	14"	Goatskin	0.7 lb.
<b>No. 1057-5</b>	High	14"	Buck Tan Cowhide	0.7 lb.
<b>No. 1050-3-1F</b>	High	12" Mitten	Cream Cowhide	0.6 lb.
<b>No. 1050-3-1FBC</b>	High	12" Mitten/Bell Cuff	Cream Cowhide	0.7 lb.



580M

581K

## RUBBER GLOVE LINERS

- Glove liners warm the hand in winter and absorb summer perspiration. One size fits all.

<b>No. 580M</b>	Mitten liner	Wt. 0.1 lb.
<b>No. 581K</b>	Liner with knit cuff	Wt. 0.1 lb.



**WARNING:** Users are responsible for specifying the correct protector length. For minimum distance requirements between the glove gauntlet and protector cuff, see ASTM F496 Table 4. Failure to maintain the proper distance between the gauntlet and cuff may cause accidental injury or death.

# RUBBER SLEEVES, CLIMBER GUARDS, AND CLEANERS



RUBBER SLEEVE

## SALISBURY LINEMEN'S RUBBER SLEEVES

- Flexible curved arm sleeves.
- Bashlin offers black and yellow/black sleeves.

	CLASS	TEST VOLTAGE	COLOR	LENGTH
<b>No. SLR-10Y</b>	1	10,000v	Yellow	26 1/2"
<b>No. SLL-10Y</b>	1	10,000v	Yellow	28"
<b>No. SLXL-10Y</b>	1	10,000v	Yellow	29 1/2"
<b>No. SLR-20B</b>	2	20,000v	Black	26 1/2"
<b>No. SLL-20B</b>	2	20,000v	Black	28"
<b>No. SLXL-20B</b>	2	20,000v	Black	29 1/2"
<b>No. SLR-20YB</b>	2	20,000v	Yellow/Black	26 1/2"
<b>No. SLL-20YB</b>	2	20,000v	Yellow/Black	28"
<b>No. SLXL-20YB</b>	2	20,000v	Yellow/Black	29 1/2"
<b>No. SLR-30Y</b>	3	30,000v	Yellow	26 1/2"
<b>No. SLL-30Y</b>	3	30,000v	Yellow	28"
<b>No. SLXL-30Y</b>	3	30,000v	Yellow	29 1/2"

**Sleeve Sizing:** Measure the distance from the top of the shoulders (between the base of the neck and the shoulder bone) to the wrist bone.



Yellow and red sleeves are available upon request. Contact us for complete information.



801

## 801 CLIMBER GUARD

- Manufactured by the dipping process using the same formulation of rubber as our lineman's insulating gloves and sleeves.
- Furnished un-slit to accommodate any length, regular or adjustable climbers.
- Sold in pairs.

**No. 801** Climber guard Wt. 1.0 lb.



SH1



SS2



SF4

## SLEEVE ACCESSORIES

<b>No. SH1</b>	Harness (1 required)	Wt. .25 lb.
<b>No. SS2</b>	Straps (1 pair required)	Wt. .20 lb.
<b>No. SF4</b>	Screw type fasteners (4 in package)	Wt. .10 lb.



805S

## GLOVE DUST

- Bashlin's glove dust lubricates while it absorbs moisture and perspiration. It will not damage natural rubber gloves.

<b>No. 805-4</b>	Glove Dust (4 - 1 quart)	Wt. 5.5 lb.
<b>No. 805S</b>	Dust filled shaker only (6 oz.)	Wt. 1.0 lb.

# GROUNDING EQUIPMENT AND POLE BAND



719

## POLE BAND

- This is a quick and easy way of marking and tagging lines during storms and routine switching. The band is easy to spot and holds a card in a weather resistant pouch with all of the necessary information.
- Secures to pole using Hook-N-Loop.

**No. 719** "WORKER ON LINE" pole band Wt. 2.0 lb.  
**No. 719-CAUTION** "CAUTION" pole band Wt. 2.0 lb.



## GROUNDING EQUIPMENT

Contact Bashlin for your grounding needs. We offer 2/0 cable and a variety of standard clamps. In addition we can help you select the correct equipment for your particular requirements.

**Please provide the following information  
and we will quote a price:**

- Location/apparatus to ground
- Clamp design and size
- Cable length
- System fault current




930T

## TRUCK GROUND

- This device will provide a quick, temporary ground when one is needed.
- A 5' rod is threaded into a ground rod driver.
- The driver can then be used to drive and remove the temporary ground.
- This device works in most rocky or frozen soil.
- The cable and clamps are not included.

**No. 930T** 5/8" threaded driver only Wt. 19.0 lb.  
**No. 930TG** Threaded driver with a 5' rod Wt. 23.0 lb.

# LINEMEN'S BLANKETS, PVC SHEETING



LB127/LB136

## LINEMEN'S BLANKETS

- These linemen's blankets are available in Type I natural rubber and Type II ozone resistant synthetic material.
- They meet or exceed all current ASTM specifications.

	TYPE	SIZE	COLOR	RATING	WT.
<b>No. LB127</b>	I	27" x 36"	Black	20,000v	6.25 lb.
<b>No. LB136</b>	I	36" x 36"	Black	20,000v	8.5 lb.
<b>No. LBS127</b>	II	27" x 36"	Orange	40,000v	6.25 lb.
<b>No. LBS136</b>	II	36" x 36"	Orange	40,000v	8.5 lb.



LBS136SL

## SLOTTED LINEMEN'S BLANKET

- These Type II blankets are available with 2" or 4 1/2" center holes.

	CTR. HOLE	SIZE	COLOR	RATING	WT.
<b>No. LBS136SL</b>	2"	36" x 36"	Orange	40,000v	8.0 lb.
<b>No. LBS136SL-4</b>	4 1/2"	36" x 36"	Orange	40,000v	8.0 lb.



LBSV118

## ZIP-ON BLANKETS

- These Type II blankets use Hook-N-Loop fasteners for easy application. They are ideal for cross arm braces and primary elbows.

	SIZE	COLOR	RATING	WT.
<b>No. LBSV118</b>	18" x 36"	Orange	40,000v	1.75 lb.
<b>No. LBSV127</b>	27" x 36"	Orange	40,000v	8.5 lb.



PVC136-50

## PVC INSULATING SHEETING

- Designed for one use only. This is an excellent alternative to standard linemen's blankets for low voltage applications.
- Tested to 10kV and meets all of the appropriate ASTM standards.

<b>No. PVC136-50</b>	Sheeting - 48" x 50" roll	Wt. 61.0 lb.
<b>No. PVC136FB</b>	Fiber storage box	Wt. 19.0 lb.
<b>No. PVC136-30</b>	36" x 30' roll	Wt. 50.0 lb.



# BLANKET CLAMPS, RESCUE STICK AND DIELECTRIC MATTING



LBC160




LBPC160

## CLAMPS

- Clamps reduce mechanical wear on blankets.

No. LBC160	8" wood clamp	Wt. 0.5 lb.
No. LBPC160	9 1/2" nylon clamp	Wt. 0.5 lb.



270

## RESCUE STICK

- This hot stick has a large radius hook. Designed to remove injured workers from electrical contact, it is tested to 100kV per foot and is 1 1/4" in diameter.

No. 270	Rescue hook - 6' long	Wt. 4.0 lb.
No. 270B	Protective bag	Wt. 1.5 lb.



700TF

## 700TF - THE FINGER

- The Finger is a safe and convenient way to lubricate your hoses. Simply clip can of silicone spray into the metal clips. When you pull your hose over "The Finger," the hose is spread, and the spray is directed into the inner skirt of the hose.
- The Finger can be mounted in your vise, fixed to the tailboard of your truck or permanently mounted inside the bin door.

No. 700TF	The Finger	Wt. 0.2 lb.
-----------	------------	-------------



DIELECTRIC MATTING

## DIELECTRIC MATTING

- This grooved matting is made for use around high voltage electric apparatus.
- It meets or exceeds the ASTM specifications.
- Type I matting, available in 20kV to 50kV rating.
- The standard widths range from 24" to 48".

PART NO.	570	571	572	573
THICKNESS	3/16"	1/4"	3/8"	1/2"
WIDTH	20KV	30KV	40KV	50KV
24"	2.6 lb./ft.	3.4 lb./ft.	5.5 lb./ft.	7.6 lb./ft.
36"	3.8 lb./ft.	5.1 lb./ft.	8.1 lb./ft.	11.3 lb./ft.
48"	5.2 lb./ft.	6.8 lb./ft.	11.0 lb./ft.	15.2 lb./ft.
FEET/ROLL	75/150	75/150	80	60



**IMPORTANT ORDERING INFORMATION:** The matting is sold in approximate lengths. This is due to the manufacturing process. There are additional charges for exact lengths, one piece rolls, or lengths less than a full roll. See the price list and contact customer service for complete information.

# INSULATING LINE HOSE, CONNECTORS, COVERS

## LINE HOSE

- Bashlin offers Type II ozone resistant line hose in straight or connector end design. This conventional line hose is available in 4 1/2' and 6' lengths.



555-24-45



550-25-45

### STRAIGHT LINE HOSE:

	SIZE	CLASS	WT.
<b>No. 550-25-45</b>	1 1/4" x 4 1/2'	2	5.75 lb.
<b>No. 550-25-6</b>	1 1/4" x 6'	2	6.0 lb.
<b>No. 550-50-45</b>	1 1/2" x 4 1/2'	3	7.0 lb.
<b>No. 550-50-6</b>	1 1/2" x 6'	3	7.0 lb.

### CONNECTOR END LINE HOSE:

	SIZE	CLASS	WT.
<b>No. 555-25-45</b>	1 1/4" x 4 1/2'	2	7.0 lb.
<b>No. 555-25-6</b>	1 1/4" x 6'	2	7.25 lb.
<b>No. 555-50-45</b>	1 1/2" x 4 1/2'	3	8.0 lb.
<b>No. 555-50-6</b>	1 1/2" x 6'	3	10.75 lb.



550-25

550-50C

### LINE HOSE CONNECTORS:

	SIZE	CLASS	WT.
<b>No. 550-25C</b>	1 1/4" x 12"	2	3.25 lb.
<b>No. 550-50C</b>	1 1/2" x 12"	3	3.0 lb.



560-2

## INSULATOR COVERS

- Salisbury Type II Insulator Covers for conventional line hose are available in 1", 1 1/4", and 1 1/2" diameters.

	INSULATOR TYPE	LINE HOSE DIAMETER	CLASS	WT.
<b>No. 560-2</b>	55-4	1"	2	7.0 lb.
<b>No. 560-3</b>	55-5	1 1/4" - 1 1/2"	3	8.0 lb.



2464



2464

## POLE GUARDS


- Made of high impact grade ABS plastic, the natural spring action holds this temporary insulation in place.
- Maximum use voltage should not exceed 26kV to ground, 44kV phase to phase, and limited to "brush" contact.

<b>No. 2464</b>	12" diagonal x 4' long	Wt. 15.0 lb.
<b>No. 2466</b>	12" diagonal x 6' long	Wt. 22.0 lb.
<b>No. 216</b>	Pole guard bag 12" x 78"	Wt. 4.0 lb.

# TRAVELING GROUNDS

The Bashlin 1590C and 336A traveling grounds reduce the possibility of electric shock due to accidental contact with energized conductors during stringing operations.

They are heavy duty units designed for conductors measuring up to and including 336MCM and 1590MCM respectively.




## 336A

No. 336A

Traveling ground


Wt. 3.0 lb.



## 336A REPLACEMENT PARTS

- This unit is designed for field repairs.
- The replacement parts are packaged to allow complete, easy replacement.

<b>No. 336A-1</b>	(A) Frame	Wt. 0.6 lb.
<b>No. 336A-2</b>	(B) Frame sheaves (2) with axle bolts, washers, and snap rings	Wt. 0.6 lb.
<b>No. 336A-3</b>	(C) Brush set (2 pc.) with springs and screws	Wt. 0.1 lb.
<b>No. 336A-4</b>	(D) Tension arm assembly, including spring, axle, snap ring, and washer (sheave is not included)	Wt. 0.7 lb.
<b>No. 336A-5</b>	(E) Ground stud (only)	Wt. .75 lb.
<b>No. 336A-6</b>	(F) Tension arm sheave with axle bolt, washer, and snap rings	Wt. 0.4 lb.
<b>No. 336A-8</b>	Carrying case (not pictured)	Wt. 0.4 lb.




## 1590C

No. 1590C

Traveling ground

Wt. 12.0 lb.



## 1590C REPLACEMENT PARTS

- This unit is designed for field repairs.
- The replacement parts are packaged to allow complete, easy replacement.

<b>No. 1590C-1</b>	(A) Frame with heli-coil	Wt. 3.75 lb.
<b>No. 1590C-2</b>	(B) Brush set (2 pc.) with springs and screws	Wt. 0.2 lb.
<b>No. 1590C-3</b>	(C) Frame sheaves (2 pc.) with axle, washers, and snap rings	Wt. 1.5 lb.
<b>No. 1590C-4</b>	(D) Yoke sheave (1 pc.) with axle, washers, and snap rings	Wt. 0.7 lb.
<b>No. 1590C-5</b>	(E) Yoke (only)	Wt. 1.5 lb.
<b>No. 1590C-6</b>	(F) Eyebolt assembly with spring, snap ring, and thrust washer	Wt. 1.5 lb.
<b>No. 1590C-7</b>	(G) Ground stud (1)	Wt. .75 lb.
<b>No. 1590C-8</b>	Carrying case (not pictured)	Wt. 0.5 lb.



**WARNING:** Test results have demonstrated the **336A** meets the short circuit requirements to be rated **Grade 3** per ASTM F885 requirements.

Test results have demonstrated the **1590C** meets the short circuit requirements to be rated **Grade 5** per ASTM F885 requirements.

Do not use these units unless the rating falls within the energy for the system on which the ground is used.







### GLOVES, PPE, BOOKS AND TRAINING

In an effort to provide for the complete needs of linemen, **Bashlin Industries, Inc.** offers products for comfort and protection from the elements. This includes top quality work gloves, and hard hats.

# KUNZ WORK GLOVES

Bashlin offers quality Kunz all leather work gloves. These gloves have been made in the USA since 1900. The Kunz glove features durable wear qualities and outstanding comfort. They are the choice, along with Bashlin products, for the professional lineworker.



556

956

## DRIVER'S GLOVE

- Developed as a quality alternative to the imported canvas-leather gloves used in light work and by machine operators.
- A major utility found that even with a higher initial cost, the wear qualities of the 956 made it an economical alternative to less expensive products.
- Specify size.

<b>No. 556</b>	Cowhide driver's glove 4" cuff	Wt. 0.5 lb.
<b>No. 956</b>	Cowhide driver's work glove	Wt. 0.5 lb.
<b>No. 956E</b>	Buckskin driver's work glove	Wt. 0.5 lb.



390

400

## FOREMAN'S GLOVE

- Bashlin stocks a medium duty foreman's glove for lighter applications. They are available in buckskin and include the "davy" tips for seam protection on the fingers.
- Specify size.

<b>No. 390</b>	Foreman's glove	Wt. 0.6 lb.
<b>No. 400</b>	Foreman's glove with gauntlet	Wt. 0.7 lb.



148

150

120

## HEAVY DUTY WORK GLOVES

- The Kunz work glove features reinforced thumb straps and outside seams with tip protectors.
- Specify size.

<b>No. 148</b>	Medium buckskin	Wt. 1.0 lb.
<b>No. 150</b>	Heavy buckskin	Wt. 1.0 lb.
<b>No. 120</b>	Heavy top grain cowhide	Wt. 1.0 lb.



145

## CLIMBING GLOVES

- Kunz trainer gloves are designed to protect the arms of the beginning climber.
- The 8" cuffs are made of heavy split cowhide, with a cotton backing, and cover most linemen nearly to the elbow reducing the chance of injury.
- Specify size.

<b>No. 145</b>	Training glove (please state numerical whole hand size)	Wt. 0.7 lb.
----------------	---	-------------

**KUNZ GLOVE  
COMPANY INC.**  
MADE IN THE USA • SINCE 1900

# EDWARDS GLOVES, KNEE PADS



B813

## LINEMEN'S PROTECTOR GLOVES

- Edwards gloves are an economical choice for your leather protector needs. These cowhide gloves meet ASTM requirements.
- Specify size.

<b>No. B813</b>	12" cowhide primary protector	Wt. 0.4 lb.
<b>No. B814</b>	13" cowhide primary protector	Wt. 0.4 lb.
<b>No. B815</b>	14" cowhide primary protector	Wt. 0.4 lb.



602A

602AT

500K

## DRIVER'S GLOVES

- Edwards cowhide work gloves provide good value for the dollar.
- Sold by the dozen.
- Specify size.

<b>No. 602A</b>	Leather driver's glove	Wt. 3.5 lb.
<b>No. 602AT</b>	Insulated driver's glove	Wt. 3.7 lb.
<b>No. 500K</b>	Canvas back glove	Wt. 3.4 lb.



B609

- Low voltage goatskin protectors are available with or without a pull strap.
- Specify size.

<b>No. B609</b>	10" goatskin protector	Wt. 0.3 lb.
<b>No. B639</b>	10" goatskin protector	Wt. 0.3 lb.



815

## KNEE PADS

- This is the original "Knee-Pro" protector. It features 1/2" foam pads, a thick plastic shell, and non-skid grips for extra comfort.

<b>No. 815</b>	Knee pads	Wt. 1.0 lb.
----------------	-----------	-------------



## SIZE:

- Sized according to the circumference of the hand below the base of the fingers, on a line parallel to the base of the finger crotches, passing through the thumb crotch. Add 1" to the measurement for the proper size.

## PLEASE PROVIDE GLOVE SIZE.

<b>SMALL:</b> 8 - 8 1/2	<b>MEDIUM:</b> 9 - 9 1/2
<b>LARGE:</b> 10 - 10 1/2	<b>X-LARGE:</b> 11 - 11 1/2

# RODEO, TRAINING PRODUCTS

Bashlin offers the official training products used at the National Linemen's Rodeo. We have been a proud sponsor and supporter of this event since 1987.



57N

57A

## POLE TOP RESCUE STRAP

- This unit helps the lineworker truly simulate cutting a victim down from a pole without destroying perfectly good equipment.
- It holds a rescue dummy in place so the rescue can be performed. Note: One set of 57A inserts are included with this unit. Additional inserts must be purchased separately.

- No. 57N** Rescue strap assembly. Two short snap/buckle sections, one double buckle section to go around the pole, and two inserts Wt. 6.0 lb.
- No. 57A** Replacement insert. One insert is 12" long with 4 holes, so it can be cut up to 3 times Wt. 0.5 lb.



**WARNING:** The 57N is only for holding a mannequin or weight in position. It is not for personnel support.



650RDB

PD100-50

PD100-38

## LINEMAN'S RODEO TOOLS

- |                     |                                  |             |
|---------------------|----------------------------------|-------------|
| <b>No. 650RDB</b>   | Ditty bag                        | Wt. 0.2 lb. |
| <b>No. PD100-38</b> | 3/8" slack block rope by the ft. | Wt. 1.0 lb. |
| <b>No. PD100-50</b> | 1/2" hand-line by the ft.        | Wt. 1.0 lb. |
| <b>No. 35</b>       | Hand-line hook                   | Wt. 0.5 lb. |
| <b>No. 960Y</b>     | 1/2" adjustable sling 28"- 48"   | Wt. 0.3 lb. |
| <b>No. 3550</b>     | Hand-line block                  | Wt. 1.2 lb. |
| <b>No. 111SK</b>    | Leather knife sheath (page 15)   | Wt. 1.0 lb. |



RR165



632RR

## RESCUE RANDY

- Official rescue mannequin of the Linemen's Rodeo.
- Lifelike, durable, articulated joints and weight distribution.
- Great for pole top and bucket rescue.

- No. RR165** 165 lb. mannequin Wt. 175.0 lb.
- No. 632RR** Waist belt for mannequin Wt. 2.0 lb.



Replacement parts for Rescue Randy are available. Contact customer service for information.



# HARD HATS/LINERS



## ME3 HARD HAT

- Features a standard style brim and a ratchet adjustment.
- Available in white, yellow, orange or blue.

<b>No. ME3-W</b>	White hard hat	Wt. 1.0 lb.
<b>No. ME3-Y</b>	Yellow hard hat	Wt. 1.0 lb.
<b>No. ME3-O</b>	Orange hard hat	Wt. 1.0 lb.
<b>No. ME3-B</b>	Blue hard hat	Wt. 1.0 lb.



## BE4: FULL BRIM HARD HAT

- Especially popular in warmer climates.
- Features a full style brim and a ratchet adjustment.
- Available in white, yellow, orange or blue.

<b>No. BE4-W</b>	White hard hat	Wt. 1.0 lb.
<b>No. BE4-Y</b>	Yellow hard hat	Wt. 1.0 lb.
<b>No. BE4-O</b>	Orange hard hat	Wt. 1.0 lb.
<b>No. BE4-B</b>	Blue hard hat	Wt. 1.0 lb.



EL27B

## HAT LINERS


- Made of flame retardant, preshrunk cotton twill.
- Thermal lined and have elastic web chin straps.
- One size fits all.
- Made in the USA.

<b>No. EL27B-0</b>	Medium length extending below the collar	Wt. .25 lb.
<b>No. EL29B-0</b>	Extra length extending below the collar	Wt. 0.4 lb.
<b>No. EL23BFM-0</b>	Medium length with a face mask, held in place with velcro fasteners	Wt. 0.4 lb.

## HARD HAT ACCESSORIES

<b>No. B304-1</b>	Sweatbands (box of 10)	Wt. 0.5 lb.
<b>No. ME91R</b>	Suspension (ratchet adjustment)	Wt. .25 lb.
<b>No. M94</b>	Chin strap	Wt. 0.4 lb.

# EDUCATION/TRAINING




831

## TEXTBOOKS

- ***The Lineman's and Cableman's Handbook***  
by Kurtz and Shoemaker  
This is the primary source of basic information for power lineworkers.

No. 831

Wt. 3.25 lb.



833

- ***Standard Handbook for Electrical Engineers***  
by Fink and Beaty  
Here is a ready reference for engineering and design of electric systems.

No. 833

Wt. 4.75 lb.



834

- ***American Electrician's Handbook***  
by Croft and Summers

If you are an electrician needing a ready, quick reference, this is the book for you.

No. 834

Wt. 4.75 lb.



Bashlin offers the most recent edition of these books. It may or may not be the one illustrated, but it will be the newest available.



## BASHLIN PRODUCT INFORMATION BOOKLETS

- Contains essential information regarding Bashlin products.
- Correct sizing, inspection, and care/maintenance of the products.
- These FREE booklets are available for the asking and are included in all new Bashlin products.

<b>No. BLCL-514</b>	Climbers and accessories	Wt. 0.1 lb.
<b>No. BLBH-514</b>	Linemen's equipment	Wt. 0.1 lb.
<b>No. PFPE-405</b>	Fall protection equipment	Wt. 0.1 lb.

## A

Adjustable Rope Slings .....	72
Aerial Bags .....	63, 64
Anchor Straps .....	50
Anchorage, Care and Maintenance .....	52
Anchorage .....	50
Auger Wind Ups .....	72

## B

Back Packs .....	58
Bags, Rodeo Ditty Bag .....	92
Bags, Back Packs .....	58
Bags, Blanket .....	61
Bags, Gear Bags .....	58, 59
Bags, Glove and Sleeve .....	60
Bags, Ground Set .....	62
Bags, Hot Stick .....	62
Bags, Nut and Bolt Bags .....	12, 13
Bags, Rescue Stick .....	62
Bags, Roller Bags .....	59
Bags, Line Hose .....	00
Belts, 2 D-Ring .....	10
Belts, 4 D-Ring .....	8, 9
Belts, Auxiliary Positioning .....	11
Belts, Care and Maintenance .....	31
Belts, Electrician .....	78
Belt, Sizing .....	6
Belts, Styles .....	7
Belts, Supporter .....	10
Belts, Suspenders .....	11
Belts, Groundman .....	78
Blanket Bags .....	61
Blanket Cannister .....	61
Blanket Clamps .....	85
Blanket Rolls .....	61
Blankets, Rubber .....	84
Blocks .....	72, 92
Booklets, Product Information .....	94
Books, Education .....	94
Bucket Cover .....	67
Bucket Hooks .....	66, 67

Bucket Knuckle .....	66
Bucket Rescue Equipment .....	55
Buckets .....	63
Bug wrenches .....	28

## C

Carabiners .....	51
Chain Hoist .....	74
Chain Saw Holder .....	67
Channel Locks .....	29
Climber Accessories .....	22, 23
Climber Guard .....	82
Climber Pad, Hook-N-Loop .....	20, 21
Climber Pads .....	20, 21
Climber Parts .....	22, 23
Climbers, Aluminum .....	18
Climbers, Steel .....	18, 19
Climbers .....	17
Climbing Harnesses .....	41
Compression Tool Bag .....	64
Confined Space Harnesses .....	42
Connectors .....	51
Cross Arm Iron .....	75
Cutters .....	76

## D

Descenders .....	51
Dielectric Harnesses .....	40
Dielectric Matting .....	85
Double Eye Slings .....	70

## E

Endless Slings .....	70
----------------------	----

## F

Fall Protection Information .....	34
Fall Restriction Device .....	24
Fixed Length Rope Slings .....	72
Folding Rules .....	30

## G

Gaff Gauge .....	23
Gaff Guards .....	23
Gaff Shaping Kit .....	23
Gaffs, Replacement .....	23
Glove Bags .....	60
Glove Dust .....	82
Gloves, Climbing .....	90
Gloves, Edwards Work Gloves .....	91
Gloves, Foreman .....	90
Gloves, Kunz Work Gloves .....	90
Gloves, Leather Protectors .....	81, 91
Gloves, Liners .....	81
Gloves, Rubber Lineman .....	80
Gloves, Sizing .....	80
Gloves, Driver .....	90, 91
Grip Slings .....	70
Ground Rod Driver .....	75
Grounding Equipment .....	75, 83, 87

## H

Hammers .....	30
Hand Tools .....	28, 29, 30
Handline Block .....	72
Handline Carrier .....	16
Handline Hooks .....	72
Handline Parts .....	72
Handlines .....	72
Hard Hat Accessories .....	93
Hard Hat Liner .....	93
Hard Hats .....	93
Harness Bag .....	64
Harnesses Arc Flash, Back Attachments .....	36
Harnesses Arc Flash, Care and Maintenance .....	35

# BASHLIN INDUSTRIES, INC. | PRODUCT INDEX

Harnesses Arc Flash, Options .....	37
Harnesses Arc Flash, Sizing .....	36
Harnesses Arc Flash, Styles .....	36, 38, 39, 40, 41, 42
Heel Cover .....	23
Hoists .....	74
Holsters, Bell Wrench .....	15
Holsters, Electrician .....	78
Holsters, Groundman .....	16
Holsters, Lineman .....	14, 15
Holsters, Lowell Wrench .....	15
Holsters, Skinning Knife .....	15
Holsters, Accessories .....	15
Hot Stick Bags .....	62
Hot Sticks .....	77

## I

Insulator Covers .....	85
------------------------	----

## K

Klein Bell Wrench .....	28
Klein Adjustable Wrenches .....	28
Klein Lineman Pliers .....	29
Knee Pads .....	911

## L

Ladder Snaphooks .....	51
Lanyards Arc Flash, Care and Maintenance .....	49
Lanyards Arc Flash, Shock Absorbing .....	43, 44, 45, 46, 47
Lanyards Arc Flash, Twin Leg .....	46, 47
Leather Care .....	16
Line, Pilot .....	73
Line, Pulling .....	73
Line, Winch Lines .....	73
Line Hose .....	86

Line Hose Bags .....	61
Line Hose Connectors .....	85
Line Hose Lubrication Tool .....	85
Lowell Ratchet Wrenches .....	28

## M

Mink Oil .....	16
----------------	----

## N

Neatsfoot Oil .....	16
Nylon Slings .....	70, 71

## P

Para-Pak .....	53
Patriot, WPFRD .....	24
Pay-Out Reels .....	75
Penta Socket .....	28
Pilot Line .....	73
Pole Band .....	83
Pole Gaffs .....	23
Pole Slings .....	70
Pole Straps .....	25
Pole Top Rescue Strap .....	92
Positioning Lanyards .....	48
Pulling Grips .....	74
Pulling Line .....	73
PVC Insulating Sheeting .....	84

## R

Replacement Gaffs .....	23
Rescue Equipment .....	53, 54, 55
Rescue Randy .....	92
Rescue Stick .....	85
Retractable Lifelines .....	56
Rodeo Products .....	92
Roller Bags .....	59
Rope .....	92
Rope, Descent Device .....	51
Rope Secondary, Care and Maintenance .....	31
Rope Secondary .....	26, 27

Rope Slings .....	71
Rope Snaphooks .....	51

## S

Saddle Soap .....	16
Safety Hook .....	67
Screwdrivers .....	30
Self Rescue Equipment .....	53, 54, 55
Shotgun Sticks .....	77
Skinning Knives .....	29
Slack Blocks .....	72
Sleeve Accessories .....	82
Sleeve Bags .....	60
Sleeves, Rubber Lineman .....	82
Splicers Bag .....	63
Staple Sticks .....	30
Strap Hoist .....	74
Suspension Trauma .....	54

## T

Tape Slings .....	16
The Finger .....	85
Tool Apron .....	66
Tool Bags .....	58, 59
Tool Boards .....	65, 66
Tool Snaps .....	16
Tool Tray .....	66
Transformer Slings .....	72
Traveling Grounds .....	87
Tree Gaffs .....	23
Truck Ground .....	83

## U

URD Disconnect Tool .....	76
---------------------------	----

## W

Winch Line .....	73
Winch Line Maintenance .....	73
Wire Basket .....	75
WPFRD .....	24



# BASHLIN INDUSTRIES, INC. | PART NUMBER INDEX

2.....	23	24HSC SERIES .....	62	53N-2HL.....	25
2SC .....	23	24RBC SERIES .....	61	54N-2HL.....	25
3.....	22	24RBR SERIES .....	61	57 SERIES.....	92
4G .....	22	24SL SERIES .....	60	76PAT .....	24
4HP .....	15	24SLGP SERIES.....	60	76PAT-OR .....	24
4HPX .....	15	25A SERIES.....	12	76PAT-ORC.....	24
4STR .....	15	25AM2 SERIES.....	12	76PAT-T.....	24
4T.....	22	25BS .....	13	78A-2HL.....	25
5.....	23	25KLBS .....	13	78B-2L.....	25
8D .....	28	25PLS .....	13	78C-2HL.....	25
10HB.....	64	25PS .....	13	78X-2HL.....	25
10S SERIES.....	58, 62	25R .....	13	80.....	11
11BP SERIES.....	58	26DRM.....	13	80HDS.....	11
11BPD SERIES .....	58	26G .....	13	80X .....	11
11BPM SERIES.....	58	26L.....	13	81.....	11
11DC SERIES.....	59	27.....	23	81-1 .....	11
12S SERIES.....	59	31L.....	16	83BDH.....	11
14.....	23	31R .....	16	83H2D .....	11
14 GLOVE SERIES.....	80	32A .....	16	85N .....	22
14ATS.....	22	32AR .....	16	85NP .....	22
14ATSB .....	22	32B .....	16	86N .....	22
14P .....	23	32BR .....	16	86NP .....	22
14T.....	23	33.....	16, 72	87N .....	22
14TS .....	22	33L.....	16, 72	87NP .....	22
14TSB .....	22	35.....	72, 92	88.....	10
15.....	30	35GP .....	72	88BIX4DCC.....	9
15FG .....	30	41NW-2HL.....	25	88BMX4D .....	9
16- GLOVE SERIES .....	80	42NW-2HL.....	25	88BMX4DCC.....	9
16ATS.....	22	43NW-2HL.....	25	88BMX4DMP .....	9
16TS .....	22	44NW-2HL.....	25		
18 GLOVE SERIES.....	80	47N-15.....	25		
18 SERIES BUCKETS .....	63	47N18 .....	25		
23 SERIES BUCKETS .....	63	51N-2HL.....	25		
24 SERIES .....	60	52N-2HL.....	25		

# BASHLIN INDUSTRIES, INC. | PART NUMBER INDEX

88BSX4DCC .....	9	111HLSX .....	14	270B .....	62, 85
88GX4DCC.....	8	111HS .....	14	300A .....	74
88GX4DMP .....	8	111HSX .....	14	300DA .....	74
88MX4DCC.....	8	111JBS .....	78	336A SERIES .....	87
88MX4DMP .....	8	111JBSX .....	78	390 GLOVE SERIES.....	90
88UX4DCC.....	8	111JLMS.....	78	400 GLOVE SERIES.....	90
88UX4DMP .....	8	111JLMSX.....	78	420G .....	29
88X .....	10	111LWH.....	15	430G .....	29
88X4D .....	9	111LWHX.....	15	443A .....	72
89N .....	22	111SK .....	15,92	470.....	72
89NP .....	22	111SKX .....	15	500K GLOVE SERIES.....	91
100TDE .....	28	111YS .....	78	550 SERIES .....	86
101TDE .....	28	111YSX .....	78	555 SERIES .....	86
103TDE .....	28	112CIL.....	78	556 GLOVES .....	90
105 PADS .....	20	112CILX.....	78	560 SERIES .....	86
110D PADS.....	21	112HLS .....	16, 78	567 SERIES .....	77
110Y GLOVE SERIES.....	80	112HLSX .....	16, 78	580M.....	81
1100Y GLOVE SERIES.....	80	120 GLOVE SERIES.....	90	581K .....	81
111BWH.....	15	130D PADS.....	21	600-12 .....	30
111BWHX.....	15	140D PADS.....	21	600-4 .....	30
111HE .....	14	140Y GLOVE SERIES.....	80	600-6 .....	30
111HEX .....	14	145 PADS .....	20	600-8 .....	30
111HLDS .....	14	145 GLOVE SERIES.....	90	602A .....	91
111HLDSE.....	14	148 GLOVE SERIES.....	90	602AT .....	91
111HLDSX.....	14	150 GLOVE SERIES.....	90	607-7DD .....	30
111HLDSXE.....	14	150-12 .....	28	625.....	78
111HLE .....	14	150T PADS .....	21	628.....	78
111HLEX .....	14	150V PADS .....	21	630.....	78
111HLS .....	14	160N .....	10	632RR .....	92
		210 SERIES .....	61	650RDB.....	92
		212 SERIES .....	61	656CM .....	10
		216.....	86	656PX .....	10
		217.....	62	662AA .....	39
		270.....	85	662AB .....	39

# BASHLIN INDUSTRIES, INC. | PART NUMBER INDEX

662AC.....	39	703R-2D.....	50	900-6.....	30
662ACS.....	42	706.....	63	901LT.....	75
662AD.....	39	706-20.....	64	901TI.....	75
662GA.....	39	706S.....	63	902 SERIES.....	75
662GD.....	39	708 SERIES.....	65, 66	903LT.....	74
662IA.....	39	712 SERIES.....	66	910 GLOVE SERIES.....	81
662ID.....	39	717.....	63	930.....	75
662RA.....	39	719.....	83	930 SERIES.....	83
662RB.....	39	719-CAUTION.....	83	930T.....	83
662RC.....	39	721AM.....	64	930TG.....	83
662RD.....	39	722AM.....	64	930UT.....	75
662VA.....	40	723AM.....	64	940 SERIES.....	72
662VD.....	40	724.....	66	945 SERIES.....	72
683GA.....	38	726.....	64	950 SERIES.....	70
683GD.....	38	727L.....	66	951 SERIES.....	70
683IA.....	38	731CS.....	67	952 SERIES.....	70
683ID.....	38	744.....	67	953 SERIES.....	70
683XA.....	38	745.....	67	956 GLOVE SERIES.....	90
683XAP.....	41	750DE SERIES.....	73	960 SERIES.....	71
683XB.....	38	750MP SERIES.....	73	960Y.....	71, 92
683XBP.....	41	770R.....	71	962 SERIES.....	71
683XC.....	38	770RDE.....	71	962NWTS.....	71
683XC6EQT.....	42	770W.....	71	965 SERIES.....	71
683XCP.....	41	801.....	82	999 GLOVE SERIES.....	81
683XD.....	38	804.....	16	1050 GLOVE SERIES.....	81
683XDP.....	41	805 SERIES.....	82	1057 GLOVE SERIES.....	81
683XDT.....	42	806 SERIES.....	16	1200 GLOVE SERIES.....	81
696NW.....	55	809.....	16	1511N.....	10
700BK.....	66	815.....	91	1515PX.....	8
700FP.....	55	831.....	94		
700FWI.....	55	833.....	94		
700TF.....	85	834.....	94		
703.....	50	884D.....	9		
703R.....	50	900 SERIES.....	75		



# BASHLIN INDUSTRIES, INC. | PART NUMBER INDEX

1515PX4D..... 8	2302 SERIES..... 45	8690FH ..... 76
1515PX4DCC..... 8	2305 SERIES..... 45	11417N..... 30
1550-4..... 29	2306 SERIES..... 45	44005..... 29
1570-3..... 29	2315 SERIES..... 45	44218..... 29
1590C SERIES..... 87	2317 SERIES..... 45	44219..... 29
1671-10..... 74	2327 SERIES..... 47	B100G-100..... 56
1672-10..... 74	2328 SERIES..... 47	B110G-25..... 56
1685-20..... 74	2464..... 86	B110G-50..... 56
1685-31..... 74	2466..... 86	B120G-30..... 56
1686-10..... 74	2802 SERIES..... 44	B120G-50..... 56
1686-20..... 74	2804 SERIES..... 44	B120G-65..... 56
1849..... 72	2805 SERIES..... 44	B130W-20..... 56
1901 SERIES..... 77	2815 SERIES..... 44	B130W-30..... 56
1967B ..... 62, 76	2817 SERIES..... 44	B1972F ..... 23
2002NWB SERIES..... 43	2827 SERIES..... 47	B1972G..... 23
2004NWB SERIES..... 43	2828 SERIES..... 47	B304-1..... 93
2005NWB SERIES..... 43	3004..... 51	B3732 ..... 50
2011 SERIES..... 70	3006..... 51	B609 ..... 91
2011P SERIES..... 50	3006K ..... 51	B6232 ..... 30
2011P1 SERIES..... 50	3008A ..... 51	B639 ..... 91
2011SE SERIES..... 70	3146..... 28	B662AA..... 40
2012 SERIES..... 70	3200..... 51	B662AD..... 40
2012P SERIES..... 50	3550..... 72, 92	B683XA..... 38
2012SE SERIES..... 70	4002NW SERIES..... 48	B683XD..... 38
2015NWB SERIES..... 43	4004NW SERIES..... 48	B809 ..... 30
2017NWB SERIES..... 43	4005NW SERIES..... 48	B813 ..... 91
2027 SERIES..... 46	4016 SERIES..... 27	B814 ..... 91
2028 SERIES..... 46	4017NW SERIES..... 48	B815 ..... 91
2028NWB SERIES..... 46	4018 SERIES..... 27	B816 ..... 30
	4019 SERIES..... 27	B832 ..... 30
	4950-58Y ..... 71	BC136 SERIES..... 61
	4951-58Y ..... 71	BC18F ..... 76
	5395A ..... 51	BC24F ..... 76
	8690CK ..... 76	BD12 SERIES ..... 19



# BASHLIN INDUSTRIES, INC. | PART NUMBER INDEX

BD12C SERIES .....	19	DEQ683XA.....	40	PD100 SERIES.....	92
BD12L SERIES.....	19	DEQ683XD1.....	40	PVC SERIES.....	84
BD14B SERIES .....	18	DL11DC-R SERIES.....	59	Q662ZA .....	41
BD16B SERIES .....	18	DL11DC-RB SERIES .....	59	Q83H2D.....	11
BD16BC SERIES .....	18	DNHLH5 .....	72	Q88BMX4D.....	9
BE4 SERIES.....	93	DSD30.....	51	Q88BMX4DCC .....	9
BED662VDEF.....	42	EL23BFM.....	93	Q88BMX4DP .....	9
BEDQ683XDI .....	42	EL27B .....	93	Q88GX4DCC .....	8
BHP .....	23	EL29B .....	93	Q88GX4DMP .....	8
BSH20.....	67	FE683EZTWR .....	41	R9074 .....	28
BSH50.....	67	FE700BMSRSC.....	55	REST .....	54
BSK20.....	29	FE700SRKSC.....	55	RESTEP .....	54
BSK25.....	29	HV208 .....	77	REST-SR.....	54
BSK30.....	29	HV212 .....	77	RJL196RCP .....	76
BSK50.....	29	HV223 .....	77	RR165 .....	92
BSS2000.....	30	HV225 .....	77	SF4 .....	82
BSS2001.....	30	HV235 .....	77	SH1 .....	82
BW221 .....	28	LB SERIES.....	84	SH200 .....	77
BW2212 .....	28	LBC160 .....	85	SH216 .....	77
BW223 .....	28	LBCP160 .....	85	SH230 .....	77
BW2237 .....	28	LBS SERIES.....	84	SL6650A .....	51
BW223HD.....	28	LBSV SERIES.....	84	SLL SERIES .....	82
BW224 .....	28	LGM2000 .....	74	SLR SERIES .....	82
BW244 .....	28	LGM4601 .....	74	SLXL SERIES .....	82
BW251 .....	28	LGM4801 .....	74	SR2804 SERIES.....	53
BW288 .....	28	LMG1000 .....	74	SR700XPL .....	53
D2000-9NE .....	29	LMG4500 .....	74	SRPACK-100AL .....	53
D2000-9NETH.....	29	LMG4501 .....	74	SS2 .....	82
D213-9BE.....	29	LMG4600 .....	74		
D507-10.....	28	LMG4800 .....	74		
D507-12.....	28	M94.....	93		
D507-8.....	28	ME3 SERIES.....	93		
DEQ662DH1 .....	40	ME91R .....	93		
DEQ662HA .....	40	PA2000 .....	74		







119 West Pine Street, P.O. Box 867 Grove City, PA 16127  
Phone: 724.458.8340 Fax: 724.458.8342 [bashlin@bashlin.com](mailto:bashlin@bashlin.com)

